

[Conventional Call Systems](#)[Call Points](#)[Standard Call Push with Protruding Button, No Reset, No Remote](#)

Standard Call Push with Protruding Button, No Reset, No Remote

Part No. NC917L

- A standard call point c/w protruding button for use with C-TEC's 800 Series Call System.
- Red reassurance LED confirms a call has been made.
- Requires a separate reset point for cancelling calls.
- Mounts on a standard UK 25mm single gang flush or surface back box.



Technical Specifications



Quiescent current	0mA.
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED (lit constant for Standard calls).
Controls	Red protruding call button (generates a Standard call when pressed). An additional 800 Series device with a reset function is required to reset this device.
Connections	SIG (Signal); -Ve (Negative).
Onboard Sounder	No.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 32 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	62g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.

Dimensions & Mounting Information		^
Product dimensions:	87 W x 87 H x 24 D mm. Mounts on a 25mm UK single gang back box.	

BIM/CAD Drawings	▼
------------------	---

Documentation	▼
---------------	---

9 other products in the same category:	▼
--	---

CONTACT US



C-TEC , Challenge Way, Wigan, WN5 0LD, UK Opening times: 08:30 - 17:00 GMT.



+44 (0) 1942 322744



sales@c-tec.co.uk



Download map
