

Plugs and connectors – Panel mounted inlets

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request. For drawings and dimensions see page 105 - 117.



Panel mounted inlet

16 A: flange 66 x 66 mm, fixing distance 52 x 52 mm, 32 A: flange 72 x 72 mm, fixing distance 60 x 60 mm, a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking
IP 44
Std. Pack. Qty: 10
Drawing: 2 MB 68

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	5			1408		
32	5			1409		



Panel mounted inlet

flange 75 x 75 mm, fixing distance 60 x 60 mm, a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

IP 44
Std. Pack. Qty: 10
Drawing: 2 MB 68/853

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	5			853		



Panel mounted inlet

nickel plated contacts, a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

IP 44
Std. Pack. Qty: 10
Drawing: 2 MB 173/2

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	3		812			
16	4		837	813	814	
16	5			815		
32	3		817			
32	4		838	819	820	
32	5			821		



Panel mounted inlet

highly heat resistant contact carrier, nickel plated contacts, a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

IP 44
Std. Pack. Qty: 5
Drawing: 2 MB 155

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
63	3		1981			
63	4		1984	1982	824	
63	5			1688		



Panel mounted inlet

nickel plated contacts, a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

IP 67
Std. Pack. Qty: 10
Drawing: 2 MB 187/2

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	3	825	826			
16	4		839	827	828	
16	5			829		
32	3	830	831			
32	4		840	832	833	
32	5			834		



Panel mounted inlet

highly heat resistant contact carrier, nickel plated contacts
63 A: a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

IP 67
Std. Pack. Qty: 5
Drawing: 2 MB 166

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
63	3	835	836			
63	4		3704	3656	3657	
63	5			3658		
125	3		3665			
125	4		3413	3583	3600	
125	5			1983		