

Terminal Boxes

Polyester Range

Polyester terminal box | MGRP

IP 66, 67



Material:

Glass fibre reinforced polyester.

Gasket:

Standard supply fitted with a polyurethane gasket. Silicone, neoprene and EPDM gaskets are available on request.

Temperature resistance:

-40 °C to +100 °C with the standard polyurethane gasket; -60 °C to +130 °C with the silicone gasket; -35 °C to +100 °C with the EPDM gasket; -30 °C to +80 °C with the neoprene gasket.

Flammability:

UL94 V-0.

Protection:

IP 66, 67.

Finish:

RAL 7000.

Approvals:

CE, GOST. For cULus_UL Listed approvals, please contact our sales department.

Delivery:

Body, door and cover screws. Cover screws manufactured from stainless steel.



Dimensional table | MGRP

IP 66, 67

Box dimension			Item no.
H	W	D	
75	80	55	MGRP080806GE
75	80	75	MGRP080808GE
75	110	55	MGRP081106GE
75	110	75	MGRP081108GE
75	160	55	MGRP081606GE
75	160	75	MGRP081608GE
75	190	55	MGRP081906GE
75	190	75	MGRP081908GE
120	122	90	MGRP121209GE
120	220	90	MGRP122209GE
160	160	90	MGRP161609GE
160	260	90	MGRP162609GE
160	360	90	MGRP163609GE
160	560	90	MGRP165609GE
250	255	120	MGRP252612GE
250	400	120	MGRP254012GE
405	400	120	MGRP414012GE

Dimensional drawing | MGRP

