


Micro Trunking 16mm x 8mm









Available in a choice of colours and with a range of Smooth-Fit accessories; the flush design gives a neat appearance.

The 16 x 8mm dimensions give options in the tightest of spaces and can often fit around door frames.





- Micro profile, only 16x8mm (WxH)
- Patented hinge & click-lock lid
- Paintable
- Smooth-Fit accessories available for perfect finish
- 'Easy to install, looks great!'
- Self-adhesive
- Fully safety tested and certified to BS EN 50085-1:2005

Code	Description	Colour
R2D1608W	(L) 2m x (W) 16mm x (H) 8mm	White
R3D1608W	(L) 3m x (W) 16mm x (H) 8mm	White
R2D1608M	(L) 2m x (W) 16mm x (H) 8mm	Magnolia
R2D1608A	(L) 2m x (W) 16mm x (H) 8mm	Aluminium Effect
R2D1608B	(L) 2m x (W) 16mm x (H) 8mm	Black
R2D16080	(L) 2m x (W) 16mm x (H) 8mm	Oak Effect

Micro Trunking 16mm x 8mm













Product Specification

Production method	Single piece design, produced in one single process by extrusion	
PVC base & lid	 Light weight, easy to handle & cut Self-extinguishing Can be drilled 	
Elastomer hinge	 Effectively bonds base & lid - lid cannot detach Impact absorbing 	
	Can be opened & closed thousands of times	
Available colours	White • Magnolia • Black • Aluminium Effect • Wood Effect	
UV stabilised	Will not discolour or turn brittle in sunlight	
Operating temperature	• Stable between -30°C upto +60°C	
½ round design	• No sharp edges	
	 Enables subtle aesthetics Blends above skirting 	
External dimensions	• 16mm x 8mm (w x h) - The smallest profile	
Таре	Foam backed 1mm thick	
	 Effective on clean dry surfaces Caution, can spoil surfaces on removal	
Paintable	Scuff using gentle abrasive such as sandpaper, so paint keys for best results	
Weight	• 0.07 kg per metre	
Packaging	Each length supplied with removable film cover	
Capacity	• If containing 240v cords leave 45% of internal capacity for air circulation	
Quality approvals	• BS EN 50085 - 1:2005 Part 1	