

Test lead/probe-in-one

Test lead and probe-in-one accessories offer the convenience of a test lead and probe-in-one unit with a variety of connections.

TL175 TwistGuard™ Test Leads

- Probes meet IEC 61010-031 requirements for safety
- Patented extendable tip guard meets CAT III 1000 V, CAT IV 600 V requirements while providing the flexibility you need for CAT II measurements
- WearGuard™ test lead wear indicator show white inner layer when leads are damaged or worn and in need of replacement
- Probes always show correct category rating for tip length being used
- Advanced strain relief exceeds 5,000 bend life
- 2 mm (0.08 in) diameter probe tips
- Available as a modular test probe under TP175 (page 10)

TL75 Hard Point™ Test Lead Set

One pair (red, black) comfort grip probes with PVC-insulated, right-angle shrouded 4 mm (0.16 in) banana plugs.

- Safety rating: CAT II 1000 V, 10 A (CAT III 1000 V, CAT IV 600 V with protective cap)



TL75



TL71

TL71 Premium Test Lead Set

One pair (red, black) comfort grip probes with flexible silicone-insulated, right-angle test leads.

- Heat and cold resistant
- Safety rating: CAT II 1000 V, 10 A (CAT III 1000 V, CAT IV 600 V with protective cap)

TL76 2mm/4mm Test Lead Set

One pair (red, black) silicone test leads with right angle shrouded 4 mm (0.16 in) banana plugs.

- Removable lantern tip for use with European wall sockets, 4 mm (0.16 in) diameter
- Removable lantern tip for easy access to terminal blocks, 2 mm (0.08 in) diameter
- GS38 probe caps (removable) allow probing in CAT II, III and CAT IV environments
- Safety rating: CAT II 1000 V, 10 A (CAT III 1000 V, CAT IV 600 V with protective cap)



TL76



TL76



TL40



TL26A

TL40 Retractable Tip Test Lead Set

One pair (red, black) flexible silicone insulated test leads with sharp needle point tips adjustable to desired length from 0 mm to 76 mm.

- Extra hard probe tips to provide long service life
- Safety rating: CAT II 600 V, 3 A rating

TL26A 60 in 5-Way Test Lead Set

One pair (red, black) silicone-insulated leads with five different ways to connect.

- U-shaped nose for blade-shaped terminals
- Notched jaw for gripping screw heads, bare wire or terminals
- Serrated teeth for gripping threaded or wire-wrapped terminals
- Sharp needle cluster for piercing small gauge (#22-#28 AWG) wires
- Large piercing needle
- Safety rating: 30 V, 10 A

TL910 Electronic Test Probes

One pair (red, black) leads with very small tips to access hard-to-reach electronic test points.

- Includes three sets of spring-loaded gold tips and two sets of stainless steel tips
- Tip length up to 100 mm (4 in)
- Tip diameter: 1 mm (0.04 in)
- Safety rating: CAT II 1000 V, 3 A