

Data Sheet.

2890/2891 Legend 305N Automatic

Part Numbers.

2890 Black

2891 Red



Product Description.

A Single chamber 275N lifejacket with Automatic operation. Fitted with UML Pro Sensor Elite® Manual Inflator and window to show the lifejacket status. Hard wearing with comfort collar. Suitable for all weather conditions, will turn the wearer over into the safe back position. Suitable for swimmers.

Approvals.

EN ISO 12402-2

Size.

One Size to fit all persons from 40Kg up to 150Kg

Chest Size 70Cm to over 175 Cm

Buoyancy 305 N when inflated

Construction.**Outer Cover.**

Fabric Heavy Duty Polyurethane coated Nylon.

Colour Black or Red

Inflatable chambers.

Fabric 210 Denier Nylon with a Polyurethane Coating that can be welded.

Colour International Orange

Visibility 6 x MED/SOLAS Retro reflective patches total 300 cm².

Cover Closure.

Burst Zip closure with two Velcro access points to access the gas system and mouth inflation tube.

Closure.

By way of 50mm polyester webbing with Heavy Duty Delrin Buckle, also fitted with twin 30mm adjustable webbing crutch strap with Acetal buckles.

General specification.

Inflation System	United Moulders Pro Sensor Elite® Manual Inflator. Or via Mouth inflation/deflation tube.
Gas Cylinders	1 x 60gm CO2, ½ thread fitted with Cylinder Safe retainer
Whistle	Orange pea-less marine grade MED/SOLAS approved
Grab Handle	25mm Nylon Webbing Integrated into lifejacket with a loop handle braided yellow on black with Grab Handle print.

Accessories.

Lifejacket Light	MED/SOLAS approved.
Spray Hood	Spray hood part no 2516 approved to EN394 Fitted with 2 x retro reflective patches and stay. High Visibility yellow with transparent PVC window.

Spare Parts.

Cylinder Kit	1 X Part no 2460 60gm CO2 cylinder.
Cartridge	1 X Part no 2520 UM Cartridge Kit.

Features.

The Legend has a clip-less firing system, and the status of the lifejacket can be seen without opening the valise via the window. The Legend is very comfortable due to the ergonomic cut and the Baltic soft fleece collar.

Storage.

The lifejacket can withstand extremes in temperature of between - 30 and + 60°C but should not be stored in direct sunlight. (please note that temperatures below 5°C can diminish the function of the lifejacket)

Service Inspection.

Lifejackets should have a daily inspection before wear with a full inspection at least annually as per the user manual.
Service life expectation: Ten years.

Maintenance and Care.

Do not use as a cushion.

After use the lifejacket should be rinsed in fresh water and dried and stored in a well ventilated area away from naked flame or hot radiators etc. Hand washing can be performed using warm water and non- biological soap powder and dried afterward as above.

Product Dimensions.

54 cm x 30 cm x 4cm weight 1.50 kg

Shipping sizes.

5 pcs per box 28 cm x 32cm x 53 cm gross weight 7.00 kg

Safety Data.

Each lifejacket contains 1 cylinder containing 60 grams of compressed Carbon Dioxide CO₂

Hazchem Code 2XE.

Pressure 56 MPa.

Hazardous UN 2990 class 9.

Country of Origin: Hungary

HS code: 6307200000

Copyright:

Baltic Safety Products AB (pub)

Box 60

S-545 02 Algaras Sweden

14/09/16 KH