

FLUXX®**-Dispensing Taps AH 23**The patented FLUXX®-Dispensing Taps for containers and drums are perfectly suitable for the simple, clean and quick decanting of fluids without

gurgling. The chamfered outlet spout also fits in narrow threaded necks and allows easy and clean

dosing.

Broad Product Program

FLUXX®-Dispensing Taps are available for all common industrial containers with standardized thread sizes ranging from DIN 45 to DIN 71 and drums with 3/4" or 2" threads.

Patented Venting System

The outstanding flow properties are based on the patented ventilation system. Thanks to this FLUXX®-Dispensing Taps AH 23 have a high flow rate of >5 L/min.

No Leaking

 $\mathsf{FLUXX}_{\$}\text{-}\mathsf{Dispensing}$ Taps are leakproof even with aggressive chemical compounds and strongly

creeping fluids.

Declaration of Conformity

All components used in the production process are uncritically in regards to EG food regulatory

guidelines 2002/72 and the German "Lebensmittel-und Futtermittel Gesetzbuch (LFGB)".

AH 23

Example



Dispensing Tap

- Fast, clean dispensing without gurgling
- Available for all common thread sizes
- Outlet spout fits into DIN 28 bottle necks and allows easy dosing even in smaller containers
- Chamfered tip for clean dispensing
- High flow rate of more than 5 L/min
- High chemical resistance
- All components are physiologicallyharmless

Dispensing of

- Chemicals
- Cleaners
- Disinfectants
- Liquid food
- Lubricants
- Water