


VP RP BP GP

HALOGEN FREE INSULATED TERMINALS

P range funnel entry - for Copper conductors



The "P" range of terminals has been designed, to meet the increasing demands for improved safety and reliability of electrical connectors.

The Polycarbonate insulation, is a Halogen free, self extinguishing thermoplastic material class V0 (UL 94). The unique funnel shaped entry of the insulation sleeve, guarantees to-


tal insertion of the conductor strands into the terminal barrel, creating a secure and reliable, electrical and mechanical connection.

The operating temperature range is - 20 to + 115°C (Surge + 130°C). Recommended crimping tools are shown on pages 108 to 129, 168.




Certified according to
EN 45545-2:2013

pin terminals




Conductor Size sqmm (AWG)	Type	Dimensions mm				Quantity Box/Bag
		Ø	B	P	L	
 0,2÷0,5 (24÷20)	VP-P10	3,0	1,0	9,8	20,2	4.000/100
	RP-P8	4,0	1,6	7,8	17,9	3.000/100
 0,25÷1,5 (22÷16)	RP-P10	4,0	1,6	9,8	19,9	3.000/100
	RP-P12	4,0	1,6	12,0	22,1	3.000/100
 1,5÷2,5 (16÷14)	BP-P8	4,9	1,7	7,8	17,9	3.000/100
	BP-P10	4,9	1,8	9,8	19,9	3.000/100
	BP-P12	4,9	1,8	11,8	21,9	2.500/100
 4÷6 (12÷10)	GP-P10	6,6	2,2	10,4	24,5	1.000/100
	GP-P12	6,6	2,2	12,6	26,7	1.000/100
	GP-P14	6,6	2,2	14,6	28,7	1.000/100

blade terminals



Conductor Size sqmm (AWG)	Type	Dimensions mm				Quantity Box/Bag
		Ø	B	P	L	
 0,2÷0,5 (24÷20)	VP-PP12/19	3,0	1,9	12,4	22,4	4.000/100
	RP-PP12	4,0	3,0	12,8	22,9	3.000/100
 0,25÷1,5 (22÷16)	RP-PP12/1	4,0	3,0	11,3	21,4	3.000/100
	RP-PP12/19	4,0	1,9	13,2	23,3	3.000/100
	RP-PP12/23	4,0	2,3	13,2	23,3	2.500/100
	RP-PP14	4,0	3,0	14,8	24,9	2.500/100
	RP-PP16/23	4,0	2,3	17,2	27,3	2.500/100
	BP-PP12	4,9	3,5	12,8	22,9	2.500/100
 1,5÷2,5 (16÷14)	BP-PP12/25	4,9	2,5	13,3	23,4	2.000/100
	BP-PP12/29	4,9	2,9	13,3	23,4	2.500/100
	BP-PP16/25	4,9	2,5	17,2	27,3	2.500/100
	GP-PP12	6,6	4,0	13,3	27,4	1.000/100
 4÷6 (12÷10)	GP-PP17	6,6	2,9	19,1	33,2	1.000/100

hooked blade terminals



Conductor Size sqmm (AWG)	Type	Dimensions mm					Quantity Box/Bag
		Ø	B	P	L	X	
 0,25÷1,5 (22÷16)	RP-PPL30*	4,0	3,0	17,5	28,3	1,7	3.000/100
	RP-PPL46*	4,0	4,6	17,5	28,3	1,7	3.000/100
 1,5÷2,5 (16÷14)	BP-PPL30*	4,9	3,0	17,5	28,3	1,7	2.500/100
	BP-PPL46*	4,9	4,6	17,5	28,8	1,7	2.500/100
 4÷6 (12÷10)	GP-PPL46*	6,6	4,6	17,5	32,6	1,9	1.000/100

*Not UL approved