


# PVC INSULATED CRIMP TERMINALS BF-PP12/29

## *blade terminals*

The unique funnel shaped PVC sleeve guarantees total insertion of the conductor strands into the terminal barrel, creating a secure and reliable, electrical and mechanical connection.

The internal surface of the barrel is rifled to improve contact with conductor strands when crimped and to increase tensile strength.

The "F" range of terminals offers a wide selection of rings, forks, pins and blades, designed to meet the ever changing end user requirements.



## Technical details:

The connectors are manufactured from electrolytic Copper Cu-ETP CWO04A according to UNI EN 13599 and are tin plated with a minimum thickness of 3µm.

Main characteristics of the PVC sleeves:

- >DIELECTRIC STRENGTH (KV/mm) : >35
- >VOLUME RESISTIVITY ( $\Omega/\text{cm}$ ) :  $>10^{15}$
- >MAX OPERATING TEMPERATURE ( $^{\circ}\text{C}$ ) : 80
- >FLAMMABILITY (UL-94) : V0
- >DENSITY ( $\text{g}/\text{cm}^3$ ) : 1,4
- >WATER ABSORPTION (%) :  $0,1 \pm 0,6$
- >BREAKING LOAD ( $\text{N}/\text{mm}^2$ ) :  $45 \pm 50$

The connectors can be stored at a minimum temperature not below - 40°C.

# PVC INSULATED CRIMP TERMINALS BF-PP12/29

## Technical characteristics

### PROPERTIES

|                                         |                     |
|-----------------------------------------|---------------------|
| Colour                                  | Blue                |
| Width                                   | 2.9 mm              |
| Length                                  | 23.3 mm             |
| Diameter                                | 4.9 mm              |
| Pack qty                                | 2,500               |
| Min. pack qty                           | 100                 |
| Pin lenght                              | 13.3 mm             |
| Dimensional form                        | Blade terminal      |
| Easy entry                              | yes                 |
| UL94 class                              | V0                  |
| Min operating temperature range         | -20 °C              |
| Max operating temperature range         | 80 °C               |
| Max operating temperature range (surge) | 90 °C               |
| Dimensional form                        | Blade terminal      |
| Material (Body)                         | Electrolytic Copper |
| Material (Partially reinforced)         | PVC                 |
| Min operating temperature range         | -20 °C              |
| Max operating temperature range         | 80 °C               |
| Max operating temperature range (surge) | 90 °C               |

