

COPPER TUBE CRIMPING LUGS A20-M

for extra flexible copper conductors

A-M series lugs are manufactured from electrolytic copper tube Cu-OF CW008A conform to UNI EN 13600.

These lugs are particularly recommended for use with extra flexible conductors on for instance, welding machines.

A-M series lugs are designed to suit panel applications.

The dimensions of the tube are designed to obtain the most efficient electrical conductivity and mechanical strength to resist vibration and pull out.

Cembre lugs are annealed to guarantee optimum ductility and electrolytically tin plated to avoid oxidation.

The presence of an inspection hole facilitates full insertion of the conductor.



CONDUCTOR TABLES IEC 60228:2004-11

CLASS 5

Nominal cross-sectional mm ²	Maximum diameter of wires in conductor mm	Maximum resistance of conductor at 20 °C	
		Plain wires [Ω/km]	Metal-coated wires [Ω/km]
0,5	0,21	39	40,1
0,75	0,21	26	26,7
1	0,21	19,5	20
1,5	0,26	13,3	13,7
2,5	0,26	7,98	8,21
4	0,31	4,95	5,09
6	0,31	3,3	3,39
10	0,41	1,91	1,95
16	0,41	1,21	1,24

25	0,41	0,78	0,795
35	0,41	0,554	0,565
50	0,41	0,386	0,393
70	0,51	0,272	0,277
95	0,51	0,206	0,21
120	0,51	0,161	0,164
150	0,51	0,129	0,132
185	0,51	0,106	0,108
240	0,51	0,08	0,081
300	0,51	0,064	0,065
400	0,51	0,048	0,049
500	0,61	0,038	0,039
630	0,61	0,028	0,029

CLASS 6


Sezione nominale mm ²	Diametro massimo dei fili mm	Resistenza massima del conduttore a 20 °C	
		Fili nudi [Ohm/km]	Fili rivestiti [Ohm/km]
0,5	0,16	39	40,1
0,75	0,16	26	26,7
1	0,16	19,5	20
1,5	0,16	13,3	13,7
2,5	0,16	7,98	8,21
4	0,16	4,95	5,09

6	0,21	3,3	3,39
10	0,21	1,91	1,95
16	0,21	1,21	1,24
25	0,21	0,78	0,795
35	0,21	0,554	0,565
50	0,31	0,386	0,393
70	0,31	0,272	0,277
95	0,31	0,206	0,21
120	0,31	0,161	0,164
150	0,31	0,129	0,132
185	0,41	0,106	0,108
240	0,41	0,08	0,081
300	0,41	0,064	0,065

COPPER TUBE CRIMPING LUGS **A20-M**

Technical characteristics

Material (Body)	ETP Copper elettrolitically tinned
Material (Seam)	ETP Copper elettrolitically tinned
Minimum section	95 mm ²
Maximum section	95 mm ²



COPPER TUBE CRIMPING LUGS A20-M

List of products

A20-M *Cable type: extra-flexible copper, Maximum section: 95 mm²*



Type	Ø Stud mm	Øi mm	B mm	M mm	N mm	L mm	d mm	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
A20-M8	8 mm	15 mm	27 mm	9 mm	8 mm	50 mm	8.4 mm	100	25	15 mm
A20-M10	10 mm	15 mm	27 mm	11 mm	10 mm	54 mm	10.5 mm	100	25	15 mm
A20-M12	12 mm	15 mm	27 mm	14 mm	12 mm	59 mm	13.2 mm	100	25	15 mm
A20-M14	14 mm	15 mm	27 mm	15.5 mm	12 mm	60.5 mm	15 mm	100	25	15 mm
A20-M16	16 mm	15 mm	27 mm	16.5 mm	13.5 mm	63 mm	17 mm	100	25	15 mm

Products used together

Accessories

INSULATED COVERS ES

ES24-BK	ES24-BR	ES24-BU
ES24-GN	ES24-GY	ES24-PK
ES24-RE	ES24-WH	ES24-YE