

MECHANICAL TOOLS TN70SE



MECHANICAL TOOLS TN70SE

Technical characteristics

PROPERTIES

Width	127 mm
Length	450 mm
Weight	2 kg
Type of action	Crimp
Material (Body)	Hardened Steel
Material (Moulded)	Plastic grips



MECHANICAL TOOLS TN70SE

Products used together

Connectors

COPPER TUBE CRIMPING LUGS A-2M

A10-2M10	A10-2M10-24-13	A10-2M12
A10-2M12-25	A10-2M6	A10-2M8
A10-2M8-20	A10-2M8-22	A10-2M8-24-24
A10-2M8-30	A14-2M10	A14-2M10-24
A14-2M12	A14-2M12-25	A14-2M12-30-29
A14-2M12-40	A14-2M14	A14-2M8
A14-2M8-24-24	A2-2M4-12	A2-2M8-20
A3-2M12-40	A3-2M8-20	A5-2M10-24-13
A5-2M8-20	A5-2M8-24-24	A7-2M10
A7-2M10-25	A7-2M12	A7-2M12-25
A7-2M12-40		

COPPER TUBE CRIMPING LUGS A-M

A10-M10	A10-M12	A10-M14
A10-M16	A10-M6	A10-M8
A14-M10	A14-M12	A14-M14
A14-M16	A14-M6	A14-M8
A1-M10	A1-M3	A1-M3.5
A1-M4	A1-M5	A1-M6
A1-M8	A2-M10	A2-M12
A2-M4	A2-M5	A2-M6
A2-M8	A3-M10	A3-M12
A3-M4	A3-M5	A3-M6
A3-M8	A5-M10	A5-M12
A5-M4	A5-M5	A5-M6
A5-M8	A7-M10	A7-M12
A7-M5	A7-M6	A7-M8

COPPER TUBE CRIMPING LUGS ANGLED 90° A-L

A10-L10	A10-L12	A10-L8
A14-L10	A14-L12	A14-L8
A1-L6	A2-L5	A2-L6
A2-L8	A3-L10	A3-L5
A3-L6	A3-L8	A5-L10
A5-L6	A5-L8	A7-L10
A7-L12	A7-L8	

RING TONGUE TERMINALS WITH CONTAINED PALM A-M Contained palm

A10B-M6/11.5	A14B-M6/11.5	A2-M5/9
A3-M5/9	A5-M5/9	A7B-M6/11.5

COPPER TUBE CRIMPING LUGS A-2M Angled

A10-2M8-24-24/345°	A14-2M10-24-26/315°	A14-2M10-24-26/345°
A14-2M12-30-29/345°	A14-2M8-24-24/345°	A5-2M12-30-29/345°
A5-2M8-24-24/345°		

COPPER TUBE CRIMPING LUGS A-M Fine stranded

A12-M10	A12-M10/19	A12-M12
A12-M6/15	A12-M8	A17-M10
A17-M10/19	A17-M12	A17-M14
A17-M16	A17-M6	A17-M8
A9-M10	A9-M12	A9-M6/15
A9-M8		

HEAVY DUTY COPPER TUBE TERMINALS 2A-M

2A10-M10	2A10-M12	2A10-M14
2A10-M16	2A14-M10	2A14-M12
2A14-M14	2A14-M16	2A3-M10
2A3-M8	2A5-M10	2A5-M12
2A5-M8	2A7-M10	2A7-M12
2A7-M8		

UNINSULATED PIN CONNECTORS A-P

A10-P25	A14-P30	A2-P12
A3-P14	A5-P16	A7-P20

Through connectors

PARALLEL CONNECTORS L-P

L10-P	L14-P	L1-P
L2-P	L3-P	L5-P
L7-P		

THROUGH CONNECTORS L-M

L10-M	L14-M	L1-M
L2-M	L3-M	L5-M
L7-M		