



YU-Lite Nickel Cadmium batteries

- Rechargeable with excellent cyclic performance
- Long service life of up to 4 years in emergency lighting applications
- Single cells & multiple pack configurations available for design flexibility
- Fully customisable – any style, connection type & voltage available upon request
- Foamed Nickel technology & 3D mesh structure for higher capacity in smaller can sizes
- High temperature versions tested to ICEL 1010
- Maintenance free
- All popular plugs, leads & tag connections available
- All standard voltage configurations available
- For industrial applications, eg emergency lighting

YU-Lite NiCd high temp D cells - most popular configurations

Cell Qty	Voltage	Capacity (Ah)	Dimensions (LxD) mm	Part Number			
				Leads	Leads & Amp Plug	Tags	Faston Tags
2	2.4	4	121x33.5	2DH4-0L4	2DH4-0LA4	2DH4-0T4	2DH4-0F4/LS
3	3.6	4	182x33.5	3DH4-0L4	3DH4-0LA4	3DH4-0T4	3DH4-0F4/LS
4	4.8	4	241x33.5	4DH4-0L4	4DH4-0LA4	4DH4-0T4	4DH4-0F4/LS
5	6	4	302x33.5	5DH4-0L4	5DH4-0LA4	5DH4-0T4	5DH4-0F4/LS
6	7.2	4	362x33.5	6DH4-0L4	6DH4-0LA4	6DH4-0T4	6DH4-0F4/LS

Style 4 (stick). Note: For packs with leads add 4mm to length.

Style 3 (side by side). Note: For packs with back plate add 3mm to width. For packs with leads add 4mm to height.

