

LOCKNUTS WITH COLLAR 1143

Polyamide PA6.6

Metric thread M 1,5 pitch CEI EN 60423




CERTIFICATES 

LOCKNUTS WITH COLLAR 1143

Technical characteristics

Material (Body)	Polyamide PA6.6
UL94 class	V2
Min operating temperature range	-20 °C
Max operating temperature range	90 °C



LOCKNUTS WITH COLLAR 1143

List of products

1143



Type	P	ØA	B	H	Pack qty	Min. pack qty	Colour
1143M12	M12X1,5	18.5 mm	17 mm	5 mm	1,000	100	Grey RAL 7035
1143M16	M16X1,5	24 mm	22 mm	5 mm	600	100	Grey RAL 7035
1143M20	M20X1,5	29 mm	27 mm	6 mm	400	100	Grey RAL 7035
1143M25	M25X1,5	35.5 mm	32 mm	6 mm	100	100	Grey RAL 7035
1143M32	M32X1,5	45 mm	41 mm	7 mm	50	50	Grey RAL 7035
1143M40	M40X1,5	55 mm	50 mm	7 mm	30	30	Grey RAL 7035
1143M50	M50X1,5	65 mm	60 mm	8 mm	30	30	Grey RAL 7035
1143M63	M63X1,5	82 mm	75 mm	8 mm	15	15	Grey RAL 7035
1143M12G	M12X1,5	18.5 mm	17 mm	5 mm	1,000	100	Dark Grey RAL 7001
1143M16G	M16X1,5	24 mm	22 mm	5 mm	600	100	Dark Grey RAL 7001
1143M20G	M20X1,5	29 mm	27 mm	6 mm	400	100	Dark Grey RAL 7001
1143M25G	M25X1,5	35.5 mm	32 mm	6 mm	100	100	Dark Grey RAL 7001
1143M32G	M32X1,5	45 mm	41 mm	7 mm	50	50	Dark Grey RAL 7001
1143M40G	M40X1,5	55 mm	50 mm	7 mm	30	30	Dark Grey RAL 7001
1143M50G	M50X1,5	65 mm	60 mm	8 mm	30	30	Dark Grey RAL 7001
1143M63G	M63X1,5	82 mm	75 mm	8 mm	15	15	Dark Grey RAL 7001
1143M12N	M12X1,5	18.5 mm	17 mm	5 mm	1,000	100	Black RAL 9005
1143M16N	M16X1,5	24 mm	22 mm	5 mm	600	100	Black RAL 9005
1143M20N	M20X1,5	29 mm	27 mm	6 mm	400	100	Black RAL 9005
1143M25N	M25X1,5	35.5 mm	32 mm	6 mm	100	100	Black RAL 9005
1143M32N	M32X1,5	45 mm	41 mm	7 mm	50	50	Black RAL 9005
1143M40N	M40X1,5	55 mm	50 mm	7 mm	30	30	Black RAL 9005
1143M50N	M50X1,5	65 mm	60 mm	8 mm	30	30	Black RAL 9005
1143M63N	M63X1,5	82 mm	75 mm	8 mm	15	15	Black RAL 9005