

# PRODUCT DATASHEET

## RF CLAS P 15 CL 1.5 W/2700 K E14

LED Retrofit CLASSIC P | LED lamps, classic mini-ball shape



### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

### Product benefits

- Very low energy consumption
- Lamps with innovative LED "filament" technology
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp

### Product features

- Professional LED lamps for line voltage
- Not dimmable
- Beam angle: up to 300°



- Lifetime: up to 15,000 h
- Lamp made of glass
- Good quality of light; color rendering index  $R_a: \geq 80$ ; constant chromaticity


## TECHNICAL DATA

## Electrical data

|  |             |
|--|-------------|
| Nominal wattage                          | 1.5 W       |
| Construction wattage                     | 1.50 W      |
| Nominal voltage                          | 220...240 V |
| Claimed equiv. conventional lamp power   | 15 W        |
| Nominal current                          | 12 mA       |
| Type of current                          | AC          |
| Inrush current                           | 2 A         |
| Operating frequency                      | 50...60 Hz  |
| Mains frequency                          | 50...60 Hz  |
| Max. lamp no. on circuit break. 10 A (B) | 416         |
| Max. lamp no. on circuit break. 16 A (B) | 666         |
| Power factor $\lambda$                   | > 0.40      |

## Photometrical data

|   |            |
|---|------------|
| Luminous flux                           | 136 lm     |
| Nominal useful luminous flux 90°        | 136 lm     |
| Luminous efficacy                       | 90 lm/W    |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Warm White |
| Color temperature                       | 2700 K     |
| Color rendering index Ra                | ≥80        |
| Light color                             | 827        |
| Standard deviation of color matching    | ≤6 sdcM    |
| Rated LLMF at 6,000 h                   | 0.80       |



## Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 300 °    |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

### Dimensions & Weight

|                  |          |
|------------------|----------|
| Overall length   | 77.00 mm |
| Diameter         | 45,0 mm  |
| Maximum diameter | 45 mm    |
| Product weight   | 15.00 g  |

### Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 50 °C        |

### Lifespan

|  |                       |
|--|-----------------------|
| Lifespan                                     | 15000 h <sup>1)</sup> |
| Number of switching cycles                   | 100000                |
| Lumen maintenance at end of service lifetime | 0.70                  |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90                |

1) L70/B50

### Additional product data

|                             |  |
|-----------------------------|--|
| Base (standard designation) | E14  |
| Mercury content             | 0.0 mg   |
| Mercury-free                | Yes  |
| Design / version            | Clear  |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|                         |                 |
|-------------------------|-----------------|
| Energy efficiency class | F <sup>1)</sup> |
| Energy consumption      | 2.00 kWh/1000h  |

|  |      |
|--|------|
| Type of protection                           | IP20 |
| Standards                                    | CE   |
| Photobiological safety group acc. to EN62778 | RG0  |

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

#### Country-specific categorizations

|                 |                               |
|-----------------|-------------------------------|
| ILCOS           | DRBP/C-1,3-827-220-240-E14-45 |
| Order reference | LEDSCLP15 1,5W/               |

#### Energy labelling regulation data acc EU 2019/2015

|   |                |
|---|----------------|
| Light source cap-type (or other electric interface) | E14            |
| Correlated colour temperature type                  | SINGLE_VALUE   |
| Length  | 77.00 mm       |
| Height  | 45,0 mm        |
| Width   | 45,0 mm        |
| EPREL ID  | 1402955,523090 |

#### DOWNLOAD DATA

| Documents and certificates  |                               |
|---|-------------------------------|
|  PDF  | Declarations Of Conformity CE |
| Photometric and lighting design files   |                               |
|  File | Spectral power distribution   |

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075434349 | Folding box 1                | 46 mm x 49 mm x 130 mm               | 27.00 g      | 0.29 dm <sup>3</sup> |
| 4052899400320 | Blister 1                    | 45 mm x 140 mm x 120 mm              | 26.00 g      | 0.76 dm <sup>3</sup> |
| 4058075605558 | Shipping box 6               | 159 mm x 111 mm x 106 mm             | 252.00 g     | 1.87 dm <sup>3</sup> |
| 4052899400337 | Shipping box 6               | 285 mm x 153 mm x 132 mm             | 310.00 g     | 5.76 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.