

technical hotline +44 (0)1268 563720

boxes and ancillary products | wiring devices

Triple Pole & Neutral Switches

32 AMP
METAL
FLUSH

SURFACE



5114WHI



5115WHI



5116WHI

Energy Saving Switch

FLUSH



4724WHI



4700WHI

Time Delay Switch

FLUSH



1610WHI

Clock Connectors

FUSED



993WHI



995WHI



997WHI

5114WHI
FLUSH MOUNTED
WITH NEON

5115WHI
SURFACE MOUNTED
WITH NEON

5116WHI
SURFACE MOUNTED
WITH NEON

4724WHI
20A DP SWITCH
WITH KEYTAG

4700WHI
SPARE KEYTAG

1610WHI
LAMP LOAD
400 WATTS MAX.
60 WATTS MIN.
AT 240V 50Hz

993WHI
SURFACE MOUNTING
suitable for installation in
small circular conduit boxes
to BS 4568 Pt.2:1970.

995WHI
FLUSH MOUNTING

997WHI
SURFACE MOUNTING

1

10

10

10

MOUNTING BOX
FLUSH: 5268ALM

These products have a utilisation category of AC22 – rated operational current (Ie), 32A – rated operational voltage (Ue), 440V. They are suitable for switching mixed resistive and inductive loads including moderate overloads.

5114 is also available in Albany Plus finishes (page 163).
All switches may be locked in the 'ON' or 'OFF' position with the use of the MK Padlock 8000.

5116 is available in Metalclad Plus version (page 214).

TERMINAL CAPACITY:
16mm² conductors. On surface mounted versions the earth terminal is fitted on base of box.

DIMENSIONS:
5114: 203 x 140mm
5115: 182 x 118 x 82mm
5116: 137 x 76 x 53mm

KNOCKOUTS:
5115: 5 x 25mm. Two top and bottom, one in back
5116: 6 x 20mm. Wiring space limits recommended cable size to 6mm².

BS EN 60947-3:1999

MOUNTING BOXES:
FLUSH: 866ZIC
SURFACE: 2160WHI

The MK Energy Saving Switch provides a simple and effective way of reducing electricity consumption while increasing safety in buildings where appliances may be left on in unoccupied rooms. By removing the keytag the power is switched off eliminating the need to switch off each individual light or appliance. A neon locator light on the switch unit makes it easy to locate when entering darkened rooms.

DIMENSIONS: 86 x 86mm
FIXING CENTRES: 60.3mm
BS EN 60669-1:1999

MOUNTING BOXES:
FLUSH: 3995ZIC-16mm deep min
SURFACE: 2140WHI-30mm deep

Adjustable 2-15 minutes. Fused at 3 amps. Multi-way. Built in neon locator.

Not suitable for fluorescent lamps or low voltage lighting systems.

DIMENSIONS:

86 x 86mm

FIXING CENTRES:

60.3mm

Fitted with 2 amp fuse-link to BS 1362.
Terminals will accommodate 2.5mm² conductors.

993WHI See page 206 for Replacement Fuse Link and Replacement Fuse Carrier 6084SL

995WHI includes earthing facilities and is suitable for mounting in BS 4662 boxes. The removable fuse carrier is fully recessed and total projection of the plate is only 4.2mm. A knockout on the underside is provided so an M3.5 screw or hook engages with a tapped lug on the box (for hanging a wall clock).

DIMENSIONS:
993WHI: 67mm diameter
995WHI: 86 x 86mm
997WHI: 65 x 65 x 32mm

FIXING CENTRES:
993WHI: 50.8mm
995WHI: 60.3mm