

Cooker Connection Unit

FLUSH



K5045WHI

Cooker Controls

45 AMP
MOULDED
FLUSH

K5060WHI



K5061WHI

45 AMP
MOULDED
SURFACE

K5040WHI



K5041WHI

45 AMP
METAL
FLUSH

K5011WHI

45 AMP
METAL
SURFACE

K5001WHI

K5045WHI**10****K5060WHI**45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET**K5061WHI**45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS**1****K5040WHI**45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET**K5041WHI**45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS**1****1****K5011WHI**45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS**1****K5001WHI**45A
DP MAIN SWITCH
AND 13A
SWITCHSOCKET OUTLET
WITH NEONS**1**

MOUNTING BOX

FLUSH:
877ZIC (46mm)Supplied complete with terminal block, each terminal of which will accommodate up to two 10mm² conductors.

Moulded cover plate, cable clamp included.

DIMENSIONS:
86 x 86mmFIXING CENTRES:
60.3mm

BS 5733: 2010

MOUNTING BOXES:

FLUSH:
886ZIC (Up to 6mm² conductor)
878ZIC (Up to 10mm² conductor)

Rotary operated shutter.

DIMENSIONS:
86 x 146mmFIXING CENTRES:
120.6mm

BS 4177: 1992

Supplied complete with mounting box and cable restraint.

Fitted with earth terminals.

Rotary operated shutter.

DIMENSIONS:
86 x 146 x 60mm

BS 4177: 1992

MOUNTING BOX

FLUSH:
5120ALM

Fitted with earth terminals.

Rotary operated shutter.

DIMENSIONS:
178 x 165mm

BS 4177: 1992

Supplied complete with mounting box.

Fitted with earth terminals.

Rotary operated shutter.

DIMENSIONS:
156 x 144 x 67mmKNOCKOUTS:
5 x 25mm.
Two in each of top and bottom,
one in back.

BS 4177: 1992