

technical hotline +44 (0)1268 563720

decorative | wiring devices

Connection Units Unswitched

13 AMP

WITH NEON
13 AMP

WITH FLEX
OUTLET
13 AMP

WITH NEON &
FLEX OUTLET
13 AMP



K14948BSS*	1	K14958BSS*	1	K14989BSS*	1	K14978BSS*	1
K14948LBS*	1	K14958LBS*	1	K14989LBS*	1	K14978LBS*	1
K14948SAA*	1	K14958SAA*	1	K14989SAA*	1	K14978SAA*	1
K14948BRC*	1	K14958BRC*	1	K14989BRC*	1	K14978BRC*	1
K14948POC*	1	K14958POC*	1	K14989POC*	1	K14978POC*	1
K14948SAG*	1	K14958SAG*	1	K14989SAG*	1	K14978SAG*	1
K14948WHIW	1	K14958WHIW	1	K14989WHIW	1	K14978WHIW	1
K14948LIVW	1	K14958LIVW	1	K14989LIVW	1	K14978LIVW	1
K14948LBKB	1	K14958LBKB	1	K14989LBKB	1	K14978LBKB	1
K14948PBR*	1	K14958PBR*	1	K14989PBR*	1	K14978PBR*	1
K14948TIRB	1	K14958TIRB	1	K14989TIRB	1	K14978TIRB	1
K14948DBZB	1	K14958DBZB	1	K14989DBZB	1	K14978DBZB	1
K14948ABSB	1	K14958ABSB	1	K14989ABSB	1	K14978ABSB	1
K14948TCOB	1	K14958TCOB	1	K14989TCOB	1	K14978TCOB	1

* Available with the option of either White or Black inserts. Add Suffix 'W' or 'B' to part number when ordering, E.g. KxxxxBSSW.

Where there is no asterisk, the final suffix W = White Insert, B = Black Insert, E.g. KxxxxWHIW = Porcelain White finish with White inserts

MOUNTING BOXES:
FLUSH 35mm: 866ZIC
FLUSH 46mm: 877ZIC
(for extra wiring space)

All connection units are fitted with a 13A fuse (to BS 1362).

TERMINAL CAPACITY:
2 x 6mm² stranded (max)

DIMENSIONS:
86 x 86mm

FIXING CENTRES: 60.3mm
BS 1363 Pt 4: 1995

MOUNTING BOXES:
FLUSH 35mm: 866ZIC
FLUSH 46mm: 877ZIC
(for extra wiring space)

All connection units are fitted with a 13A fuse (to BS 1362).

TERMINAL CAPACITY:
2 x 6mm² stranded (max)

DIMENSIONS:
86 x 86mm

FIXING CENTRES: 60.3mm
BS 1363 Pt 4: 1995

MOUNTING BOXES:
FLUSH 35mm: 866ZIC
FLUSH 46mm: 877ZIC
(for extra wiring space)

All connection units are fitted with a 13A fuse (to BS 1362).

TERMINAL CAPACITY:
2 x 6mm² stranded (max)

DIMENSIONS:
86 x 86mm

FIXING CENTRES: 60.3mm
BS 1363 Pt 4: 1995

MOUNTING BOXES:
FLUSH 35mm: 866ZIC
FLUSH 46mm: 877ZIC
(for extra wiring space)

All connection units are fitted with a 13A fuse (to BS 1362).

TERMINAL CAPACITY:
2 x 6mm² stranded (max)

DIMENSIONS:
86 x 86mm

FIXING CENTRES: 60.3mm
BS 1363 Pt 4: 1995