

technical hotline +44 (0)1268 563720

decorative | wiring devices

2 GANG SP
2 WAY
20 AMP
WITH LARGE
ROCKERS

High Current
Switches

1 GANG DP
WITH NEON
32 AMP

1 GANG DP
WITH NEON
50 AMP

Cooker
Control Unit

45 AMP DP
MAIN SWITCH
AND 13 AMP
SWITCH SOCKET
OUTLET WITH
NEONS

3 Pole Fan
Isolator

32A
Triple Pole
& Neutral
Switch



K13472BSS* 1	K14305BSS* 1	K14336BSS* 1	K14361BSS* 1	K14859BSS* 1	K14114BSS* 1
K13472LBS* 1	K14305LBS* 1		K14361LBS* 1	K14859LBS* 1	K14114LBS* 1
K13472SAA* 1	K14305SAA* 1		K14361SAA* 1	K14859SAA* 1	K14114SAA* 1
K13472BRC* 1	K14305BRC* 1		K14361BRC* 1	K14859BRC* 1	K14114BRC* 1
K13472POC* 1	K14305POC* 1		K14361POC* 1	K14859POC* 1	K14114POC* 1
K13472SAG* 1	K14305SAG* 1		K14361SAG* 1	K14859SAG* 1	K14114SAG* 1
K13472WHIW 1	K14305WHIW 1		K14361WHIW 1	K14859WHIW 1	K14114WHIW 1
K13472LIVW 1	K14305LIVW 1		K14361LIVW 1	K14859LIVW 1	K14114LIVW 1
K13472LBKB 1	K14305LBKB 1		K14361LBKB 1	K14859LBKB 1	K14114LBKB 1
K13472PBR* 1	K14305PBR* 1		K14361PBR* 1	K14859PBR* 1	K14114PBR* 1
K13472TIRB 1	K14305TIRB 1		K14361TIRB 1	K14859TIRB 1	K14114TIRB 1
K13472DBZB 1	K14305DBZB 1		K14361DBZB 1	K14859DBZB 1	K14114DBZB 1
K13472ABSB 1	K14305ABSB 1		K14361ABSB 1	K14859ABSB 1	K14114ABSB 1
K13472TCOB 1	K14305TCOB 1		K14361TCOB 1	K14859TCOB 1	K14114TCOB 1

* Available with the option of either White or Black inserts. Add Suffix 'W' or 'B' to part number when ordering, E.g. KxxxxBSSW.

Where there is no asterisk, the final suffix W = White Insert, B = Black Insert, E.g. KxxxxWHIW = Porcelain White finish with White inserts

MOUNTING BOXES:
FLUSH: 861ZIC

DIMENSIONS:
86 x 86mm

ROCKER DIMENSIONS:
22 x 40mm

FIXING CENTRES:
120.6mm

BS 60669-1:1999

These switches do not have to be derated when used with fluorescent or inductive loads

MOUNTING BOXES:
FLUSH: 866ZIC

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS EN 60669-1: 1999

These switches do not have to be derated when used with fluorescent or inductive loads.

MOUNTING BOXES:
FLUSH: 866ZIC

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS EN 60669-1: 1999

These switches do not have to be derated when used with fluorescent or inductive loads.

MOUNTING BOXES:
FLUSH: 878ZIC

45A DP Main Switch and 13A Switchsocket outlet with NEONS (Up to 10mm² conductor).

Rotary operated shutter.

DIMENSIONS:
86 x 146mm

FIXING CENTRES:
120.6mm

BS 4177: 1992

To allow adequate wiring space, mounting box must be installed 6mm to 10mm sub flush to the wall surface.

MOUNTING BOXES:
FLUSH: 877ZIC

DIMENSIONS:
86 x 186mm

FIXING CENTRES:
60.3mm

BS EN 60947-3:1999

To allow adequate wiring space, mounting box must be installed 6mm to 10mm sub flush to the wall surface.

MOUNTING BOXES:

FLUSH: 5268ALM (Mounting box should be mounted 6 to 10mm sub-flush to the wall)

DIMENSIONS:
203 x 140mm

TERMINAL CAPACITY:
16mm² conductors

BS EN 60947-3: 1999

NOT RECOMMENDED FOR SWITCHING
LARGE BANKS OF PCS