

technical hotline +44 (0)1268 563720

decorative | wiring devices

1 GANG DP  
LOCKABLE  
FIRE ALARM  
ISOLATOR  
SWITCH  
20 AMP

Shaver/  
Toothbrush  
Supply Units

DUAL VOLTAGE  
OUTPUT 115/230V  
INPUT 220/240V  
50/60HZ

120/130V INPUT  
(NON UK)



**K14379BSS**

**1**

Only available in  
Brushed Stainless Steel



**K14709BSS\***

**1**



**K14710BSS\***

**1**

**K14709LBS\***

**1**

**K14710LBS\***

**1**

**K14709SAA\***

**1**

**K14710SAA\***

**1**

**K14709BRC\***

**1**

**K14710BRC\***

**1**

**K14709POC\***

**1**

**K14710POC\***

**1**

**K14709SAG\***

**1**

**K14710SAG\***

**1**

**K14709WHIW**

**1**

**K14710WHIW**

**1**

**K14709LIVW**

**1**

**K14710LIVW**

**1**

**K14709LBKB**

**1**

**K14710LBKB**

**1**

**K14709PBR\***

**1**

**K14710PBR\***

**1**

**K14709TIRB**

**1**

**K14710TIRB**

**1**

**K14709DBZB**

**1**

**K14710DBZB**

**1**

**K14709ABSB**

**1**

**K14710ABSB**

**1**

**K14709TCOB**

**1**

**K14710TCOB**

**1**

\* Available with the option of either White or Black inserts. Add Suffix 'W' or 'B' to part number when ordering, E.g. KxxxxBSSW.

Where there is no asterix, the final suffix W = White Insert, B = Black Insert, E.g. KxxxxWHIW = Porcelain White finish with White inserts

MOUNTING BOX:  
FLUSH 46mm: 877ZIC

DIMENSIONS:  
86 x 86mm

FIXING CENTRES:  
60.3mm

BS 60669-2-4: 2005

The isolator has primarily been introduced for use in alarm systems that must comply with BS 5839 Part 1

MOUNTING BOXES:  
FLUSH: 878ZIC

This design incorporates a double wound isolating transformer rated 20VA at 230 or 115 volts and meets BS EN 61558-2-5: 1998, making it safe for use in bathrooms.

Insertion of a shaver/toothbrush plug automatically switches on output by energising the primary side of the isolating transformer – removal automatically switches it off. The transformer is protected against overload by an automatic solid state overload device with automatic resetting.

DIMENSIONS: 146 x 86mm

FIXING CENTRES: 120.6mm

BS EN 61558-2-5: 1998

