



Swifts® cable tray fittings


SS light duty, MRF medium duty, SRF heavy duty, XRF extra heavy duty



Universal bracket
MRFUB PG



Universal bracket
SRFUB PG



Universal fishplate
UF 450 F



Dimensions and technical information **p. 51, 69, 105**

Pack	Cat. Nos.	Fittings
		Universal brackets and fishplates are used for on-site fabrication of fittings
		Universal bracket Universal brackets can be used in a number of ways to achieve many change of direction and reducing functions Brackets can be folded into shape using a pair of pliers to create bends, tees, 4 way crosspieces etc
		Over fold to split bracket and join using fasteners to create hinged couplers
5	MRFUB F	For MRF tray
5	SRFUB F	For SRF tray Supplied in packs containing 5 pairs of brackets, 100 quick bolt fasteners, and power tool nut driver Available in PG, G and S finishes For technical information, p. 51, 69

Pack	Cat. Nos.	Fittings (continued)
		Universal fishplates Fishplates are designed for extra strength when joining cable tray beds They can also help to protect cables from cut edges The universal fishplate can be overfolded and split at 75 mm centres when working with narrow trays Can be used in conjunction with universal bracket, p. 51, 69 Available in PG, G and S finishes
1	UF450 F	
		Fishplates Fishplates are designed for extra strength when joining cable tray beds Supplied singly without fasteners To select correct fishplate, refer to table p. 105
1	F F	For SS and XRF
1	MF F	For XRF
1	WF F	For SS, MRF, SRF and XRF For technical information, p. 105

Key : selecting fittings. Replace the letters shown in **red** with your choice from the following options :

F = Finish : **G** (hot dip galvanised after manufacture),
D (deep galvanised), **PG** (pre-galvanised)
S (stainless steel)