Inspiration starts here

PRODUCT SELECTOR

INTELLIGENT DIMMERS		DIMMERS		GRID PLUS FRONT PLATES		
1 GANG SINGLE 2 WAY DIMMER 40W/VA-300W/ 240VA INC. 4-70W LED, 230V~50HZ	1 GANG DOUBLE 2 WAY DIMMER 40W/VA-300W/ 240VA INC. 4-70W LED, 230V~50HZ	1 GANG SINGLE 2 WAY DIMMER 100W-1000W, 230V~50HZ (NON UK)	1 GANG SINGLE 2 WAY DIMMER 100W-1000W, 230V~60HZ (NON UK)	1 MODULE GRID FRONTPLATE	2 MODULE GRID FRONTPLATE	
9	20	J	9			

FUNCTIONAL MODULES							
White	MH1523WHILV	MH1524WHILV	MH1561WHI	MH1661WHI	MH4331WHIC	MH4332WHIC	
Black	MH1523BLKLV	MH1524BLKLV	MH1561BLK	MH1661BLK	MH4331BLKC	MH4332BLKC	

FRONTPLATES								
METAL FINISHES**								
Brushed Stainless Steel (BSS)	MHFP033BSS*	MHFP034BSS*	MHFP033BSS*	MHFP033BSS*	MHFP001BSS*	MHFP002BSS*		
Satin Steel (SST)	MHFP033SST*	MHFP034SST*	MHFP033SST*	MHFP033SST*	MHFP001SST*	MHFP002SST*		
Satin Brass (SBR)	MHFP033SBR*	MHFP034SBR*	MHFP033SBR*	MHFP033SBR*	MHFP001SBR*	MHFP002SBR*		
Bronze (BRZ)	MHFP033BRZ*	MHFP034BRZ*	MHFP033BRZ*	MHFP033BRZ*	MHFP001BRZ*	MHFP002BRZ*		
SYNTHETIC FINISHES								
White (WHI)	MHFP033WHI	MHFP034WHI	MHFP033WHI	MHFP033WHI	MHFP001WHI	MHFP002WHI		
Light Silver (LTS)	MHFP033LTS	MHFP034LTS	MHFP033LTS	MHFP033LTS	MHFP001LTS	MHFP002LTS		
Dark Silver (DKS)	MHFP033DKS	MHFP034DKS	MHFP033DKS	MHFP033DKS	MHFP001DKS	MHFP002DKS		
Champagne (CHM)	MHFP033CHM	MHFP034CHM	MHFP033CHM	MHFP033CHM	MHFP001CHM	MHFP002CHM		

MOUNTING BOXES
35MM
866ZIC
DIMENSIONS
866Mm
FIXING CENTRES
60.3mm
BSEN 60669-2-1:2004

MOUNTING BOXES
35MM
866ZIC
DIMENSIONS
86 x 86mm
FIXING CENTRES
60.3mm
BSEN 60669-2-1:2004

MOUNTING BOXES
35MM
866ZIC
DIMENSIONS
86×86mm

86 x 86mm FIXING CENTRES 60.3mm BSEN 60669-2-1:2004 MOUNTING BOXES
35MM
866ZIC
DIMENSIONS
86 x 86mm

FIXING CENTRES 60.3mm BSEN 60669-2-1:2004 MOUNTING BOXES
35MM
891ALM
DIMENSIONS
86 x 86mm
BS 5733:2010

MOUNTING BOXES 35MM 891ALM DIMENSIONS 86 x 86mm BS 5733:2010

These dimmers employ the latest micro-controller based circuitry to provide electronic soft-start and overload protection. They are suitable for use with good quality electronic or wire-wound transformers. Can also be used with good quality halogen lamps incorporating GU10 bases. Please check with lamp manufacturer to determine suitability.

NOT SUITABLE FOR FLUORESCENT LOADS

Conform to latest standards BS EN 60669-2-1. All intelligent dimmers have a combined push-on/push-off switch and rotary dimmer control, and are suitable for one or two-way switching. Only one dimmer can be used in a two way switching circuit.

NOTE

Grid frontplates include an integral grid mounting frame. See page xx for full range of Grid Functional modules.