

Robust cable reel enables various appliances to be connected at one time.

The cable can be easily retracted using the wind handle. It is practical with the reel being able to stand up and the handle allowing easy transportation. Ideal for professional use on site, at home or in the workshop

► Case Reels

Standard of Compliance -

BS 61242:1998

Specification -

• 3 x 15mm² cable • 4 Outlets

• 13A 3120W Unwound Rating • Thermal Cut-Out

List No.	Description	Pack Qty
HCR42013	20m case reel	1



► Open Reels

Standard of Compliance -

BS 61242:1998

Specification -

• 3 x 15mm² cable • 4 Outlets

• 13A 3120W Unwound Rating • Thermal Cut-Out

List No.	Description	Pack Qty
NER42513	25m Open reel	1
NER45013	50m Open reel	1



► 2 Gang - 13A



Standard of Compliance - **BS 1363 & BS 1361**

List No.	Description	Pack Qty
RS213CPW	2 gang + 2m cable	1
RS213/3CPW	2 gang + 3m cable	1
RS213/5CPW	2 gang + 5m cable	1

► 4 Gang - 13A

Standard of Compliance - **BS 1363 & BS 1361**

List No.	Description	Pack Qty
RS413/3CPW	4 gang + 3m cable	1
RS413/5CPW	4 gang + 5m cable	1



► 4 Gang Switched - 13A



Standard of Compliance - **BS 1363 & BS 1361**

List No.	Description	Pack Qty
RS413SCPW	4 gang + 2m cable, switched	1

► 4 Gang 4 Switches - 13A

Standard of Compliance - **BS 1363 & BS 1361**

List No.	Description	Pack Qty
RS413ICPW	4 gang + 2m cable, 4 switches	1



► 6 Gang - 13A



Standard of Compliance - **BS 1363 & BS 1361**

List No.	Description	Pack Qty
RS613CPW	6 gang + 2m cable	1