

technical hotline +44 (0)1268 563720

decorative | wiring devices

20 AMP
SP 2 WAY
& CENTRE OFF
LATCHING

20 AMP
SP 2 WAY
RED ROCKER
& CENTRE OFF
LATCHING

20 AMP
INTERMEDIATE

20 AMP
INTERMEDIATE
RED ROCKER

20 AMP
DP
1 WAY

20 AMP
DP
1 WAY
WITH NEON


K4899BSS* 1	K4899RED 10	K4893BSS* 1	K4893RED 10 K4893REDB 10	K4896BSS* 1	K4896NWHI 1 K4896NBLK 1
K4899LBS* 1		K4893LBS* 1		K4896LBS* 1	
K4899BRC* 1		K4893BRC* 1		K4896BRC* 1	
K4899POC* 1		K4893POC* 1		K4896POC* 1	
K4899SAG* 1		K4893SAG* 1		K4896SAG* 1	
K4899WHIW 1		K4893WHIW 1		K4896WHIW 1	
K4899LIVW 1		K4893LIVW 1		K4896LIVW 1	
K4899LBKB 1		K4893LBKB 1		K4896LBKB 1	
K4899PBR* 1		K4893PBR* 1		K4896PBR* 1	
K4899TIRB 1		K4893TIRB 1		K4896TIRB 1	
K4899DBZB 1		K4893DBZB 1		K4896DBZB 1	
K4899ABSB 1		K4893ABSB 1		K4896ABSB 1	
K4899TCOB 1		K4893TCOB 1		K4896TCOB 1	

* Available with the option of either White or Black inserts. Add Suffix 'W' or 'B' to part number when ordering, E.g. KxxxxBSSW.

Where there is no asterisk, the final suffix W = White Insert, B = Black Insert, E.g. KxxxxWHIW = Porcelain White finish with White inserts

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 1999

These switches do NOT have to be derated when used with inductive loads.

Note: Push switches are not designed for fluorescent loads.

BS EN 60669-1: 1999

Not available in other finishes

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 1999

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 1999

Not available in other finishes

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 1999

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 1999

Not available in other finishes