

Inspiration starts here
PRODUCT SELECTOR

EURO MULTIMEDIA MODULES

SINGLE OUTLET
 (IEC MALE)
 1 MODULE
 25 X 50MM



SINGLE OUTLET
 (IEC FEMALE)
 1 MODULE
 25 X 50MM



SINGLE F-TYPE
 SATELLITE
 SOCKET
 1 MODULE
 25 X 50MM



FEMALE HDMI OUTLET
 2 MODULE
 50 X 50MM



FUNCTIONAL MODULES

White	K5850WHI	K5851WHI	K5855WHI	K5807WHI
Black	K5850BLK	K5851BLK	K5855BLK	K5807BLK

Fully screened non isolated TV outlets containing a combination of single, TV/FM Diplexer, TV/FM/SAT Triplexer and BT secondary telephone outlets for use within digital TV systems and interactive TV services.

Single outlets for connection to a single TV, FM or Satellite co-axial aerial lead.

MOUNTING BOXES

Min box depth 47mm

DIMENSIONS

ONE MODULE 25 x 50mm

TWO MODULE 50 x 50mm

BS 3041:1997, IEC 169-2:1965, BS EN 50083 & BS 5733:2010 where applicable.

NOTE

These products are fully compatible with Labgear TV distribution systems and are approved for use in "Sky Homes" and "Homes On" specifications.

K5807 Female HDMI Outlet is HDMI 1.1, 1.2, 1.3 and 1.4b compatible, HDCP compliant.

DATA RATE

Up to 2.25 Gbps

SCAN

Up to 1080p/1920 x 1200

INPUT CONNECTOR

1 x HDMI Female (Type A)

OUTPUT CONNECTOR

1 x HDMI Female (Type A)

Supports high resolution input:

PC: VGA, SVGA,

SXVGA (1280 x 1024) and UXGA

(1600 x 1200, 1920 x 1200)

HDTV: 480p, 720p, 1080i and 1080p

HDMI input cable should be no larger

than 20m

DIMENSIONS

50 x 50 x 20mm

Mains operated products and extra low voltage modules must not be installed within the same frontplate.

Refer to BS 7671:2008 for details.