

technical hotline +44 (0)1268 563720

decorative | wiring devices

High Current Switches

WITH FLEX
OUTLET
AND NEON
FLUSH

32 AMP
FLUSH

50 AMP
FLUSH



Cooker Control Units

45 AMP
DP MAIN
SWITCH AND 13
AMP SWITCH
SOCKET OUTLET
WITH NEONS
FLUSH



Triple Pole & Neutral Switch

32 AMP
WITH NEON
FLUSH



Shaver/Toothbrush Supply Units

DUAL VOLTAGE
115/230V
OUTPUT
(220/240V
50/60HZ INPUT)
FLUSH



K5250BSS	5	K5106BSS	5	K5236BSS	5	K5261BSS	5	K5114BSS	5	K703BSS	5
K5250BRC	5	K5106BRC	5	K5236BRC	5	K5261BRC	5	K5114BRC	5	K703BRC	5
K5250SAG	5	K5106SAG	5	K5236SAG	5	K5261SAG	5	K5114SAG	5	K703SAG	5
K5250PCR	5	K5106PCR	5	K5236PCR	5	K5261PCR	5	K5114PCR	5	K703PCR	5

DP Switches are
not recommended
for switching large
banks of PCs

MOUNTING BOXES:
FLUSH:
866ZIC (6mm² conductors)
877ZIC (10mm² conductors)
SURFACE (BRC) :
WITH KNOCKOUTS:
K899ALM
WITHOUT KNOCKOUTS:
K829ALM
DIMENSIONS:
86 x 86mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 1999

MOUNTING BOXES:
FLUSH:
886ZIC (6mm² conductors)
878ZIC (10mm² conductors)
SURFACE (BRC)
WITH KNOCKOUTS
K897ALM
WITHOUT KNOCKOUTS
K830ALM
DIMENSIONS:
86 x 146mm
FIXING CENTRES:
120.6mm
BS EN 60669-1: 1999

MOUNTING BOXES:
FLUSH:
886ZIC
(Up to 6mm² conductor)
878ZIC
(Up to 10mm² conductor)
Rotary operated shutter.
DIMENSIONS:
86 x 146mm
FIXING CENTRES:
120.6mm
BS 4177: 1992

MOUNTING BOX:
FLUSH: 878ZIC
This product is rated at
440 volts with a motor load
rating of up to 12kW – 16 HP
at 415V 3 phase.
It has a utilisation category of
AC22A – switching of mixed
resistive and inductive loads
including moderate overloads
for a continuous duty of 32
amps. Making capacity is 2000
amps peak.
TERMINAL CAPACITY:
16mm² conductors.
DIMENSIONS:
146 x 86mm
BS EN 60947-3: 1992

MOUNTING BOXES:
FLUSH: 878ZIC
This design incorporates
a double wound isolating
transformer rated 20VA at 230
or 115 volts and meets
BS EN 61558-2-5:1998 making
it safe for use in bathrooms.
Insertion of a shaver/toothbrush
plug automatically switches on
by energising the primary side
of the isolating transformer –
removal automatically switches
off. The transformer is protected
against overload by an
automatic solid state overload
device with automatic resetting.
DIMENSIONS: 146 x 86mm
FIXING CENTRES: 120.6mm
BS EN 61558-2-5: 1998