

Connection Units

SWITCHED FUSED

DP SWITCHED
WITH FLEX OUTLET
FLUSH

DP SWITCHED
FLUSH

DP SWITCHED
WITH
TAMPERPROOF
FUSE
CARRIER SCREW
FLUSH

DP SWITCHED
WITH NEON
FLUSH



FINISHES

BRUSHED STAINLESS STEEL	K931BSS	5	K941BSS	5	K941KOBSS	5	K961BSS	5	K961D6BSS	5
BRUSHED CHROME	K931BRC	5	K941BRC	5	K941KOBRC	5	K961BRC	5	K961D6BRC	5
SATIN GOLD	K931SAG	5	K941SAG	5	K941KOSAG	5	K961SAG	5	K961D6SAG	5
POLISHED CHROME	K931PCR	5	K941PCR	5	K941KOPCR	5	K961PCR	5	K961D6PCR	5

MOUNTING BOXES:

FLUSH: 866ZIC

SURFACE (BRC):

WITH KNOCKOUTS: K899ALM

WITHOUT KNOCKOUTS:

K829ALM

All connection units are fitted with a 13A fuse (to BS 1362)

TERMINAL CAPACITY: 2 x 6mm² stranded (max)

DIMENSIONS: 86 x 86mm

FIXING CENTRES: 60.3mm

BS 1363 Pt 4: 1995