

technical hotline +44 (0)1268 563720

decorative | wiring devices

DP SWITCHED
WITH FLEX
OUTLET AND
NEON
FLUSH



DP SWITCHED
WITH FLEX
OUTLET AND
NEON
FLUSH



DP SWITCHED
WITH FLEX
OUTLET,
NEON AND
TAMPERPROOF
FUSE
CARRIER SCREW
FLUSH




Connection Units
UNSWITCHED FUSED

WITH
TAMPERPROOF
FUSE CARRIER
SCREW
FLUSH



WITH
TAMPERPROOF
FUSE CARRIER
SCREW
FLUSH



K971BSS	5	K971D6BSS	5	K971KOBSS	5	K948BSS	5	K948KOBSS	5
K971BRC	5	K971D6BRC	5	K971KOBRC	5	K948BRC	5	K948KOBRC	5
K971SAG	5	K971D6SAG	5	K971KOSAG	5	K948SAG	5	K948KOSAG	5
K971PCR	5					K948PCR	5	K948KOPCR	5

MOUNTING BOXES:

FLUSH: 866ZIC

SURFACE (BRC) :
WITH KNOCKOUTS:
K899ALM

WITHOUT KNOCKOUTS:
K829ALM

All connection units are fitted with a
13A fuse
(to BS 1362)

TERMINAL CAPACITY
2 x 6mm² stranded (max)

DIMENSIONS: 86 x 86mm

FIXING CENTRES: 60.3mm

BS 1363 Pt 4: 1995