


Switchsocket Outlets


2 GANG DP
WITH NEONS
FLUSH



2 GANG DP
WITH OUTBOARD
ROCKERS AND
DUAL EARTH
TERMINALS
FLUSH



2 GANG DP
WITH OUTBOARD
RED ROCKERS AND
DUAL EARTH
TERMINALS
FLUSH



2 GANG DP
WITH OUTBOARD
ROCKERS AND
'CLEAN EARTH'
FACILITY
FLUSH



1 GANG DP
WITH
CLEAN EARTH
FACILITY
FLUSH



FINISHES

BRUSHED STAINLESS STEEL	K2448BSS	5	K2947BSS	5	K2947D6BSS	5	K2947CEBSS	5	K1258BSS	10
BRUSHED CHROME	K2448BRC	5	K2947BRC	5	K2947D6BRC	5	K2947CEBRC	5		
SATIN GOLD	K2448SAG	5	K2947SAG	5						
POLISHED CHROME	K2448PCR	5	K2947PCR	5			K2947CEPCR	5	K1258PCR	10

High Integrity Earthing

K2958, K2458, K2947

Fitted with two earth terminals to provide a double earth facility for use when installations require a high integrity protective connection as specified within BS 7671: 2008.

K2947CE

This product is provided with facilities for 'clean earth' connection.

BS 1363 Pt 2: 1995

K1258, K1259, These products are provided with facilities for 'clean earth' connection and are suitable for non standard plugs with 'T' shaped earth pin. See page 224.

BS 1363 Pt 2: 1995 where relevant

MOUNTING BOXES:

FLUSH 25mm

1 GANG: 861ZIC

2 GANG: 862ZIC

FLUSH 35mm (for extra wiring space)

1 GANG: 866ZIC

2 GANG: 886ZIC

SURFACE WITH KNOCKOUTS

1 GANG: K899ALM

2 GANG: K897ALM

SURFACE WITHOUT KNOCKOUTS

1 GANG: K829ALM

2 GANG: K830ALM

DIMENSIONS:

1 GANG: 86 x 86mm

2 GANG: 86 x 146mm

FIXING CENTRES:

1 GANG: 60.3mm

2 GANG: 120.6mm

BS 1363 Pt 2: 1995

Double pole switching

All switchsockets have double pole switching (neutral makes first, breaks last).