

technical hotline +44 (0)1268 563720

white | wiring devices

TV/FM and Satellite Co-Axial Socket Outlets

FOR DIGITAL AND INTERACTIVE SERVICES
SCREENED, NON ISOLATED
FLUSH

TV/FM and Satellite Co-Axial Socket Outlets with Telephone Outlet

FOR DIGITAL AND INTERACTIVE TV SERVICES
FLUSH



K3550WHI



K3551WHI



K3555WHI



K3552WHI



K3552DABWHI



K3553WHI



K3553DABWHI



K3554DABWHI



K3557WHI



K3561WHI



K3561DABWHI



K3562WHI



K3563WHI



K3563DABWHI



K3564DABWHI



K3565DABWHI



K3566DABWHI

K3550WHI

SINGLE OUTLET
(IEC MALE)

10

K3551WHI

SINGLE OUTLET
(IEC FEMALE)

10

K3555WHI

SINGLE OUTLET
F-TYPE SATELLITE SOCKET

10

K3552WHI

TWIN TV/FM
DIPLEXER

10

K3552DABWHI

TWIN TV/FM
DAB DIPLEXER

10

K3553WHI

TRIPLE TV/FM/SAT
TRIPLEXER

10

K3553DABWHI

TRIPLE TV/FM DAB/SAT
TRIPLEXER

10

K3554DABWHI

QUAD TV/FM DAB/SATX2
QUADPLEXER

10

K3557WHI

SINGLE OUTLET (IEC MALE)
WITH TELEPHONE SECONDARY

10

K3561WHI

TRIPLE TV/FM/SAT TRIPLEXER
WITH TELEPHONE SECONDARY

5

K3561DABWHI

TRIPLE TV/FM DAB/SAT TRIPLEXER
WITH TELEPHONE SECONDARY

5

K3562WHI

TWIN TV/FM DIPLEXER
WITH SINGLE TV (IEC MALE)
AND TELEPHONE SECONDARY

5

K3563WHI

TRIPLE TV/FM/SAT TRIPLEXER
WITH SINGLE TV (IEC MALE)
AND TELEPHONE SECONDARY

5

K3563DABWHI

TRIPLE TV/FM/DAB/SAT TRIPLEXER
WITH SINGLE TV (IEC MALE)
AND TELEPHONE SECONDARY

5

K3564DABWHI

QUAD TV/FM DAB/SATX2 QUADPLEXER
WITH TELEPHONE SECONDARY

5

K3565DABWHI

QUADPLEXER + RJ45
AND TELEPHONE SECONDARY

5

K3566DABWHI

QUADPLEXER
WITH TELEPHONE SECONDARY
AND SINGLE TV (IEC MALE)

5

Fully screened non isolated TV outlets containing a combination of single, TV/FM Diplexer, TV/FM/SAT Triplexer and secondary telephone outlets for use within digital TV systems and interactive TV services.

Single outlets for connection to a single TV, FM or Satellite co-axial aerial lead. TV/FM diplexer units for connection to a single co-axial aerial lead with combined TV and FM signals.

TV/FM/SAT triplexer units for connection to a single co-axial aerial lead with combined TV, FM and Satellite signals

Telephone Secondary outlet for use with interactive TV digital services.

K3562 and K3563 outlets with additional single TV (male) outlet for secondary distribution of TV signal

MOUNTING BOXES:
Minimum box depth 32mm
1 gang: Flush: 866ZIC
Surface: K2181WHI
2 gang: Flush: 886ZIC
Surface: K2183WHI

DIMENSIONS:
1 gang: 86 x 86mm
2 gang: 86 X 146mm

FIXING CENTRES:
1 gang: 60.3mm
2 gang: 120.6mm

PERFORMANCE
SINGLE OUTLETS
TV/FM IEC MALE OR FEMALE
DC-950MHz
SAT F-TYPE
DC-950MHz

TV/FM/SAT PRODUCTS
OUTLET TV
DIPLEXER
5-65MHz
470-862MHz
FM/DAB
SAT
87.5-108MHz
N/A

TV/FM/DAB/SAT PRODUCTS FOR DIGITAL RADIO
OUTLET TV
DIPLEXER
5-65MHz
470-862MHz
FM/DAB
SAT OR SAT1
SAT2
87.5-230MHz
N/A

OUTLET TV
TRIPLEXER
5-65MHz
470-862MHz
87.5-108MHz
950-2300MHz

OUTLET TV
TRIPLEXER
5-65MHz
470-862MHz
87.5-230MHz
950-2300MHz
5-2300MHz

BS 3041: 1997
IEC169-2: 1965
BS EN 50083 where applicable
BS 5733: 2010 where applicable
BS 6312 Pt2