



CEILING ACCESSORIES

RANGE INTRODUCTION

MK Electric offers a comprehensive range of white ceiling accessories for all requirements. Included in the range are enhanced 'safety' lampholders.

Unlike most other 'safety' lampholders, when the lamp is removed Shockguard Plus automatically shields the contact by means of a specially designed shutter and it remains that way until a lamp is replaced.

Therefore when no lamp is in place contact pins are totally isolated, eliminating danger of electrocution.

FEATURES & BENEFITS

EASE OF INSTALLATION

Pendant sets incorporate a heat resistant lampholder, ceiling rose with a transparent base and clear terminal markings for ease of identification. Terminals are grouped in line with neutral, loop-in and earth terminals.

SAFETY

Shockguard Plus has a specially designed shutter that automatically shields the lamp contacts, therefore eliminating the danger of electrocution.

RELIABILITY

All products are 100% tested before delivery for confidence, so a 'fit and forget' installation can be achieved. Fully compliant with the relevant British Standards BS 7895 for bayonet lampholders with enhanced safety and BS EN 61184.

DURABILITY

Manufactured from the highest quality materials to give a high gloss finish, which is both scratch and colour fade resistant.

Ceiling Accessories

Lampholders

SG TYPE



1150WHI

1150WHI
BC PENDANT
SG TYPE LAMPHOLDER

10

Shockguard SG Type lampholders automatically shield contacts by means of a shutter when the lamp is removed. All MK SG Type lampholders are heat resistant to category T2 of BS EN 61184 and are therefore capable of operation with lamp cap temperatures up to 210°C.
BS EN 61184:1997
BS 7895:1997

Pendant Sets

SG TYPE



K1186WHI

K1189WHI

K1186WHI
150MM PENDANT SET
K1189WHI
230MM PENDANT SET

10

10

K1186WHI and **K1189WHI** incorporate a lampholder (K1170WHI), heat resisting PVC insulated and sheathed flexible 0.75mm² two core circular cable complying with BS EN 50525-2-11 and a ceiling rose fitted with line, neutral, loop-in and earth terminals (K1161WHI). This assembly will support a light fitting of up to 3kgs.



1146WHI

1149WHI

1146WHI
SG TYPE
150MM PENDANT SET
1149WHI
SG TYPE
230MM PENDANT SET

10

10

1146WHI and **1149WHI** incorporate a SG lampholder (1150WHI), heat resisting PVC insulated and sheathed flexible 0.75mm² two core circular cable complying with BS EN 50525-2-11 and a ceiling rose fitted with line, neutral, loop-in and earth terminals (1174WHI). This assembly will support a light fitting of up to 3kgs.

Batten Lampholders

SG TYPE



K1172WHI

K1172WHI
BC ANGLED
1174WHI
HEAT RESISTANT TAILS,
LIVE, NEUTRAL, LOOP-IN
AND EARTH TERMINALS

10

10

All MK lampholders are heat resistant to category T2 of BS EN 61184 and are therefore capable of operation with lamp cap temperatures up to 210°C.

1174WHI also incorporates heat resistant wires connecting the terminals in the base to the lampholder. It has terminals mounted in the base and knockouts which accommodate 3 x 2.5 mm² cables and allow for off centre cable entries.
BS EN 61184:1997 T2 Rated.



1152WHI

1152WHI
SG TYPE
ANGLED BATTEN
LAMPHOLDER
HEAT RESISTANT TAILS,
LIVE, NEUTRAL, LOOP-IN
AND EARTH TERMINALS
1154WHI
SG TYPE
BATTEN LAMPHOLDER
HEAT RESISTANT TAILS,
LIVE, NEUTRAL, LOOP-IN
AND EARTH TERMINALS

10

10

Shockguard SG Type lampholders automatically shield contacts by means of a shutter when the lamp is removed.

All MK SG Type lampholders are heat resistant to category T2 of BS EN 61184 and are therefore capable of operation with lamp cap temperatures up to 210°C.

1152WHI and **1154WHI** also incorporate heat resistant wires connecting the terminals in the base to the lampholder.
BS EN 61184:1997 T2 Rated.
BS 7895:1997