

DATA SHEET: 10KVA SITEMASTER 240V

PART NUMBER	10KSITE240C
TYPE	DOUBLE WOUND & EARTH SCREEN
LOADING / RUNNING CYCLE	CONTINUOUS USE
KVA RATING	10
INPUT VOLTAGE	240V SINGLE PHASE
INPUT AMP LOAD	42A
OUTPUT VOLTAGE	110V CTE
OUTPUT AMP LOAD	91A
INCOMING PROTECTIVE DEVICES	NONE - INTERNAL TERMINALS
OUTGOING PROTECTIVE DEVICES	2X20A & 2X32A DPMCB C curve
INPUT AUXILIARY (APP INLET ETC)	NONE - INTERNAL TERMINALS
OUTPUT AUXILIARY (SOCKETS ETC)	4x16A & 2x32A 110V Sockets
FREQUENCY	50/60 Hz
COOLING	DRY, AIR COOLED
INSULATION	CLASS F
ENCLOSURE TYPE	10KVA SITE MASTER IP44
ENCLOSURE OUTER DIMENSIONS	H650 x W465 x D464mm
WEIGHT	70kg

CONFORMS TO BS EN 61558 PARTS 1, 2-4
(WHERE APPLICABLE) 2-23. WITH AN
EARTHED SECONDARY WINDING

REDUCED LOW VOLTAGE
TRANSFORMER
IN ACCORDANCE WITH BS7671.



REPRESENTATIVE IMAGE

TRANSPOWER
ENGINEERING

