

DATA SHEET: 10KSITE3PHC 3PH SITEMASTER

PART NUMBER	10KSITE3PHC
TYPE	DOUBLE WOUND & EARTH SCREEN
LOADING / RUNNING CYCLE	CONTINUOUS USE
KVA RATING	10
INPUT VOLTAGE	415V 3PHASE
INPUT AMP LOAD	13.9A
OUTPUT VOLTAGE	110V (63.5V L-E)
OUTPUT AMP LOAD	52.48A
INCOMING PROTECTIVE DEVICES	NONE HARDWIRED
OUTGOING PROTECTIVE DEVICES	4X16A & 2X32A DP C CURVE MCB
INPUT AUXILIARY (APP INLET ETC)	NONE - INTERNAL TERMINALS
OUTPUT AUXILIARY (SOCKETS ETC)	4x16A & 2x32A 110V IP44 Sockets
FREQUENCY	50/60 Hz
TYPE	DRY, AIR COOLED
INSULATION	CLASS F
ENCLOSURE TYPE	10KVA SITE MASTER IP44
ENCLOSURE OUTER DIMENSIONS	H 650 X W 605 X L 464mm
WEIGHT	90kg
ADDITIONAL ITEMS	RLV-REDUCED LOW VOLTAGE
EXTRA DPMCB'S AND/OR SOCKETS	TRANSFORMER IN ACCORDANCE
CAN BE FITTED ON REQUEST	WITH BS7671



TRANSPOWER
ENGINEERING

REPRESENTATIVE IMAGE

