

Nylon pull-wire fix ed endings pulling eye and flexible head with pulling eye 20 m Ø 4 mm without casing

Suitable for passing through unobstructed environments.



Caracteristics

Length (m) : 20
Pull-wire Ø (mm) : 4
Breakage (kg) : 70

Benefits

- Very flexible.
- Low shape memory.

GENERAL INFORMATION

Technical details

Hexagonal crimping.

Includes:

Flexible head with screwed pulling eye, M5 Ø 6 mm .

Screwed pulling eye, M5 Ø 6 mm.

Advice

Maximum bending diameter, 4 cm.

Application(s)

For pulling cables through 16 to 25 mm electrical ducts and conduits.

Ideal for distances up to 20 m.

LOGISTIC INFORMATION

Packaging



Color sticker

Height (cm) : 30

Length (cm) : 30

Depth (cm) : 3

Net weight (kg) : 0,305

Gross weight (kg) : 0,305



3 700882 122520

Outer package 1



x 35

Carton box

Height (cm) : 60

Length (cm) : 32

Depth (cm) : 32

Net weight (kg) : 10,7

Gross weight (kg) : 11,4



3 700882 131126

Outer package 2



x 420

Pallet

Height (cm) : 113

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 128,1

Gross weight (kg) : 148,7



3 700882 131164