

Multi-purpose Tigre® beam clip 2-8 mm (x 80)



Characteristics

Length (mm) : 28
 Width (mm) : 19
 Height (mm) : 30
 Hole Ø (mm) : 6.6
 Material thickness (mm) : 2-8
 Tensile strength (daN*) : 120
 Quantity per box : 80

Benefits

- Easy to use: quick and simple installation.
- Compatible with fixings for IRL tubes.

GENERAL INFORMATION

Description

Multi-usage rapid fixing system.

Technical details

Galvanised steel with anti-corrosion protection.
 Salt spray resistance (h): 600.

Advice

Identify the fixing orientation by putting the eye guide upwards.

Application(s)

For installation and suspension of cable routes, light fixings, ventilation and air conditioning on IPN/IPE beams. Compatible with S-shape suspension hooks (BIZ 710 170, BIZ 710 173), threaded rods (BIZ 710 200, BIZ 720 200, BIZ 710 201, BIZ 720 201), rods, cables (BIZ 710 350, BIZ 710 351, BIZ 710 352, BIZ 710 353) and Ø 9 mm cable collars.

Instructions

1. Can be installed by hand or using only a hammer.

LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm) : 13
 Length (cm) : 18,8
 Depth (cm) : 12,3
 Net weight (kg) : 0,572
 Gross weight (kg) : 0,769



Outer package 1



x 6.00

Carton box

Height (cm) : 21
 Length (cm) : 39
 Depth (cm) : 28
 Net weight (kg) : 3,432
 Gross weight (kg) : 5,007

