

## Bi-metal CLIC II hole saw Ø 48 mm



## Characteristics

Ø (mm) : **48**  
 Depth of cut (mm) : **44**  
 Steel (tr/min) : **300-170**  
 Stainless steel (tr/min) : **175-85**  
 Recommended speed in wood and PVC (tr/min) : **2500-2000**

## Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard
- ✓ Stainless steel

## GENERAL INFORMATION

## Description

Supplied without arbor or pilot drill.

## Technical details

Material: HSS steel with 8% cobalt.  
Teeth per inch: 4/6.

## Advice

Do not use with hammer mode.

## Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

## Instructions


- To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

## ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

## ACCESSORIES



Hex. arbor for Clic II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clic II hole saw 120 mm

## LOGISTIC INFORMATION

## Packaging



## Blister package

Height (cm) : 16,6  
 Length (cm) : 8,6  
 Depth (cm) : 5,8  
 Net weight (kg) : 0,15  
 Gross weight (kg) : 0,4



## Outer package 1



x 6

## Carton box

Height (cm) : 18  
 Length (cm) : 20,7  
 Depth (cm) : 13,2  
 Net weight (kg) : 2,4  
 Gross weight (kg) : 2,485



## Outer package 2



x 72

## Carton box

Height (cm) : 40  
 Length (cm) : 60  
 Depth (cm) : 40  
 Net weight (kg) : 10,8  
 Gross weight (kg) : 12,81



## Outer package 3



x 864

## Pallet

Height (cm) : 135  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 129,6  
 Gross weight (kg) : 167,2

