

Cross Line Laser Level with stand



Characteristics

Numbers of beams : **2**
 Maximum span (m) : **30**
 Precision (mm/m) : **0.2**
 Unit of measure : **m**
 Temperature in use (°C) : **-10/+45**
 Weight (g) : **620**

Norms

✓ IP 54

Benefits

- Compact, easy to put in a tool box.



GENERAL INFORMATION

Description

Class II laser level with projections of horizontal and vertical lines intersecting at 90°.
Indoor and outdoor use.
Supplied with storage pouch and instruction manual.

Technical details

Shock-absorbing bimaterial rubber casing.
'Tilt' mode for angle tracing and marking.
Sturdy folding feet for angle positioning and height adjustment.
Self-levelling mechanism.
Visual and sound 'out of range' alarm.
1/4 threading (adapts to tripod BIZ 700 388).
Power supply: 3 AA batteries (not supplied).
Dimensions: 100 x 82 x 104 mm.
Weight: 620 g.

Application(s)

For the horizontal and vertical alignment of electrical sockets, switches, cables, pipes, worktops, wall coverings, radiator brackets, etc.

Instructions

1. Use possible outdoors, 50 m range using a detector.



ACCESSORIES



Tripod for lasers BIZ 700 276, BIZ 782 276 and BIZ 700 394



LOGISTIC INFORMATION

Packaging

**Cardboard box with window****Height (cm) :** 16,1**Length (cm) :** 12,9**Depth (cm) :** 12,6**Net weight (kg) :** 0,548**Gross weight (kg) :** 0,548

3 700882 135599

Outer package 1



x 12.00

Carton box**Height (cm) :** 16,5**Length (cm) :** 77**Depth (cm) :** 26,5**Net weight (kg) :** 6,576**Gross weight (kg) :** 8,55

3 700882 144133

Outer package 2



x 288.00

Pallet**Height (cm) :** 114**Length (cm) :** 120**Depth (cm) :** 80**Net weight (kg) :** 157,824**Gross weight (kg) :** 204,45

3 700882 144140