

Double grip tape black 25 mm x 2 m x 5.4 mm



Characteristics

Length (m) : 2
Width (mm) : 25
Thickness (mm) : 5.4

Benefits

- No drill required.
- Re-openable.
- Convenient roll format.
- Excellent resistance to humidity.



GENERAL INFORMATION

Description

Strong adhesive tape coated with plastic studs which interlock when pressed.

This system can be used for invisible, openable and re-usable attachments.

The double tape guarantees a reliable and fast attachment with no need for a drill.

Technical details

Maximum load resistance: 3.5 kg/cm².

Stud density per cm²: 42.

Resistance to temperature: -30 to +90 °C.

Installation temperature: +15 to +30 °C.

Advice

Optimal grip after 36 hours.

Application(s)

Workshop set-up, installation of panels to access cables, attach cable trays, office equipment, etc.

Instructions

1. Clean grease and dust carefully from the surfaces.
2. Cut 2 strips to the required length.
3. Apply strong pressure to the strips for 30 seconds.
4. Press the 2 strips together and make sure you hear a click guaranteeing a secure grip.
5. To open, separate the 2 strips by pulling.



LOGISTIC INFORMATION

Packaging

**Carton box**

Height (cm) : 25
Length (cm) : 14,5
Depth (cm) : 14,5
Net weight (kg) : 0,09
Gross weight (kg) : 0,11



3 700882 152985

Outer package 1



x 10

Carton box

Height (cm) : 30
Length (cm) : 15,5
Depth (cm) : 15,5
Net weight (kg) : 1,1
Gross weight (kg) : 1,24



3 700882 154194

Outer package 2



x 1700

Pallet

Height (cm) : 155
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 210,8
Gross weight (kg) : 220,8



3 700882 154200