



Suspension lock \varnothing 1.5-2.5 mm (x 75)

All-in-one versatility and practicality!



Characteristics

Length (mm) : **37.5**
 Width (mm) : **23.8**
 Thickness (mm) : **13**
 Use : **Interior**
 Quantity per box : **75**

Benefits

- Up to 6 times faster installation than a typical suspension system.
- Easy and quick adjustment without specific tool!
- New streamlined, discrete and light design.

GENERAL INFORMATION

Technical details

Housing: ZA2 zinc.
 Wedge: hardened steel, minimum Rockwell 56C.
 Spring: type 302 stainless steel.
 Cover: UV-stabilised PP.
 Button: PP reinforced with 33% fibreglass.
 APAVE test report available on request.

Advice

Observe the maximum and minimum usage loads.
 Check that the cable has no traces of oil, paint or rust.
 Do not use outside or in a chlorinated, marine or corrosive environment.
 Do not use for hoisting.
 Use only for suspension of equipment under static load.
 Do not use to splice two cables.
 Do not use for suspension of more than 60° from the vertical axis.
 Leave a minimum of 75 mm of cable trailing from the lock.

Application(s)

For suspending or securing fastening of cable trays, light fixtures, ventilation ducts, pre-wired electrical distribution ducts, centre points, signs, etc.
 Compatible with steel cables \varnothing 1.5 mm (BIZ 710 350 and BIZ 710 351) and \varnothing 2.5 mm (BIZ 710 352 and BIZ 710 353).

Instructions

1. Arrows indicating the cable entry and exit direction for safe, easy and quick implementation of suspension loops.
2. Unlocking by simple pressure.
3. Quick adjustment of the length or modification once the object to be hanged is in place.

LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm) : 10
 Length (cm) : 13,5
 Depth (cm) : 9
 Net weight (kg) : 1,88
 Gross weight (kg) : 1,96



3 700882 164889

Outer package 1



Carton box

Height (cm) : 13
 Length (cm) : 41
 Depth (cm) : 27
 Net weight (kg) : 11,76
 Gross weight (kg) : 12,74



3 700882 166715

x 6

Outer package 2



Pallet

Height (cm) : 100
 Length (cm) : 80
 Depth (cm) : 60
 Net weight (kg) : 518
 Gross weight (kg) : 536



3 700882 166722

x 180