


# Bi-metal CLIC II hole saw Ø 21 mm



## Characteristics

**Ø (mm): 21**  
**Depth of cut (mm): 44**  
**Steel (tr/min): 580-300**  
**Stainless steel (tr/min): 300-175**  
**Recommended speed in wood and PVC (tr/min): 3000-2500**

## Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard
- ✓ Stainless steel

## GENERAL INFORMATION

### Description

Supplied without arbor or pilot drill.

### Technical details

Material: HSS steel with 8% cobalt.  
Teeth per inch: 4/6.

### Advice

Do not use with hammer mode.

### Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

### Instructions


1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

## ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

## ACCESSORIES



Hex. arbor for Clic II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clic II hole saw 120 mm



## LOGISTIC INFORMATION

## Packaging

**Blister package**

Height (cm) : 16,6

Length (cm) : 5,2

Depth (cm) : 5,2

Net weight (kg) : 0,062

Gross weight (kg) : 0,062



3 700882 171816

## Outer package 1



x 6.00

**Carton box**

Height (cm) : 18

Length (cm) : 20,7

Depth (cm) : 13,2

Net weight (kg) : 0,372

Gross weight (kg) : 0,474



3 700882 171269

## Outer package 2



x 72.00

**Carton box**

Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

Net weight (kg) : 4,464

Gross weight (kg) : 6,708



3 700882 172051

## Outer package 3



x 864.00

**Pallet**

Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 53,568

Gross weight (kg) : 98,592



3 700882 172525