


Clc II bimetal hole saw Ø 27



Characteristics

Ø (mm): **27**

Depth of cut (mm): **44**

Steel (tr/min): **580-300**

Stainless steel (tr/min): **300-175**

Recommended speed in wood and PVC (tr/min): **3000-2500**

Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard
- ✓ Stainless steel

GENERAL INFORMATION

Description

Supplied without arbor or pilot drill.

Technical details

Material: HSS steel with 8% cobalt.

Teeth per inch: 4/6.

Advice

Do not use with hammer mode.

Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

Instructions


1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

ACCESSORIES



Hex. arbor for Clc II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clc II hole saw 120 mm



LOGISTIC INFORMATION

Packaging

**Blister package**

Height (cm) : 16,6

Length (cm) : 6,7

Depth (cm) : 5,2

Net weight (kg) : 0,091

Gross weight (kg) : 0,11



3 700882 171030

Outer package 1



x 6

Carton box

Height (cm) : 18

Length (cm) : 20,7

Depth (cm) : 13,2

Net weight (kg) : 0,66

Gross weight (kg) : 0,745



3 700882 171283

Outer package 2



x 72

Carton box

Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

Net weight (kg) : 8,94

Gross weight (kg) : 10,448



3 700882 172075

Outer package 3



x 864

Pallet

Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 125,376

Gross weight (kg) : 148,376



3 700882 172549