


## Bi-metal CLIC II hole saw Ø 35 mm



## Characteristics

Ø (mm): **35**

Depth of cut (mm): **44**

Steel (tr/min): **300-170**

Stainless steel (tr/min): **175-85**

Recommended speed in wood and PVC (tr/min): **2500-2000**

## Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard
- ✓ Stainless steel

## GENERAL INFORMATION

## Description

Supplied without arbor or pilot drill.

## Technical details

Material: HSS steel with 8% cobalt.

Teeth per inch: 4/6.

## Advice

Do not use with hammer mode.

## Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

## Instructions


1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

## ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

## ACCESSORIES



Hex. arbor for Clic II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clic II hole saw 120 mm



## LOGISTIC INFORMATION

## Packaging

**Blister package**

Height (cm) : 16,6

Length (cm) : 6,7

Depth (cm) : 5,2

Net weight (kg) : 0,127

Gross weight (kg) : 0,127



3 700882 171078

## Outer package 1



x 6.00

**Carton box**

Height (cm) : 18

Length (cm) : 20,7

Depth (cm) : 13,2

Net weight (kg) : 0,762

Gross weight (kg) : 0,882



3 700882 171320

## Outer package 2



x 72.00

**Carton box**

Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

Net weight (kg) : 9,144

Gross weight (kg) : 11,604



3 700882 172112

## Outer package 3



x 864.00

**Pallet**

Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 109,728

Gross weight (kg) : 157,344



3 700882 172587