


## Bi-metal CLIC II hole saw Ø 43 mm



## Characteristics

Ø (mm): **43**

Depth of cut (mm): **44**

Steel (tr/min): **300-170**

Stainless steel (tr/min): **175-85**

Recommended speed in wood and PVC (tr/min): **2500-2000**

## Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard
- ✓ Stainless steel

## GENERAL INFORMATION

## Description

Supplied without arbor or pilot drill.

## Technical details

Material: HSS steel with 8% cobalt.

Teeth per inch: 4/6.

## Advice

Do not use with hammer mode.

## Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

## Instructions


1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

## ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

## ACCESSORIES



Hex. arbor for Clic II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clic II hole saw 120 mm



## LOGISTIC INFORMATION

 Packaging**Blister package**

Height (cm) : 16,6

Length (cm) : 7,4

Depth (cm) : 5,2

 Net weight (kg) : 0,148 Gross weight (kg) : 0,168 Outer package 1

x 6

**Carton box**

Height (cm) : 18

Length (cm) : 20,7

Depth (cm) : 13,2

 Net weight (kg) : 1,008 Gross weight (kg) : 1,093 Outer package 2

x 72

**Carton box**

Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

 Net weight (kg) : 13,116 Gross weight (kg) : 14,624 Outer package 3

x 864

**Pallet**

Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

 Net weight (kg) : 175,488 Gross weight (kg) : 198,488