


Bi-metal CLIC II hole saw Ø 102 mm



Characteristics

Ø (mm): 102
Depth of cut (mm): 44
Steel (tr/min): 110-52
Stainless steel (tr/min): 55-40
Recommended speed in wood and PVC (tr/min): 1500-1000

Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard
- ✓ Stainless steel

GENERAL INFORMATION

Description

Supplied without arbor or pilot drill.

Technical details

Material: HSS steel with 8% cobalt.
 Teeth per inch: 4/6.

Advice

Do not use with hammer mode.

Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

Instructions


1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

ACCESSORIES



Hex. arbor for Clic II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clic II hole saw 120 mm


LOGISTIC INFORMATION
Packaging

Blister package
Height (cm) : 21,5

Length (cm) : 16,1

Depth (cm) : 9,5

Net weight (kg) : 0,462

Gross weight (kg) : 0,462

3 700882 171214
Outer package 1


x 4.00

Carton box
Height (cm) : 23

Length (cm) : 33,2

Depth (cm) : 19,7

Net weight (kg) : 1,848

Gross weight (kg) : 2,224

3 700882 171467
Outer package 2


x 16.00

Carton box
Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

Net weight (kg) : 7,392

Gross weight (kg) : 9,632

3 700882 172259
Outer package 3


x 192.00

Pallet
Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 88,704

Gross weight (kg) : 133,68

3 700882 172723