

Multi-material CLIC II hole saw Ø 92 mm



Characteristics

Ø (mm): **92**

Recommended speed in wood and chipboard panels (tr/min): **300**

Recommended speed in tile (tr/min): **250**

Materials

- ✓ Cellular concrete
- ✓ Wood
- ✓ Plasterboard
- ✓ Hollow brick
- ✓ Solid brick

GENERAL INFORMATION

Description

Supplied without arbor or pilot drill.

Technical details

Cutting depth (mm): 59.
Tungsten carbide tips.
Wide ejection notches.

Advice

Do not use with hammer mode.


Application(s)

Ideally suited to hard and natural wood, plaster boards, plaster blocks, hollow and solid bricks, floor tiling and cellular concrete, etc.
Not suited for concrete and construction materials such as concrete blocks.

Instructions

1. **According to the material to drill**, fit on a shaft for CLIC II hole saws BIZ 780 150 or BIZ 780 151 and fitted with a pilot drill BIZ 780 153 or BIZ 780154.


ACCESSORIES



Hex. arbor for Clic II hole saw with HSS pilot drill 120 mm



Hss pilot drill for Clic II hole saw 120 mm



Carbide tipped pilot drill for Clic II hole saw 120 mm



LOGISTIC INFORMATION

Packaging

**Blister package**

Height (cm) : 18,3

Length (cm) : 12,2

Depth (cm) : 9,5

Net weight (kg) : 0,484

Gross weight (kg) : 0,518



3 700882 170149

Outer package 1



x 8

Carton box

Height (cm) : 23

Length (cm) : 33,2

Depth (cm) : 19,7

Net weight (kg) : 4,144

Gross weight (kg) : 4,328



3 700882 171993

Outer package 2



x 32

Carton box

Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

Net weight (kg) : 17,312

Gross weight (kg) : 18,82



3 700882 172464

Outer package 3



x 384

Pallet

Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 225,84

Gross weight (kg) : 248,84



3 700882 172938

SPECIMEN