

CHRISTA'L push wire connector 2 way purple (x 100)**Characteristics**Number of inputs : **2**Colour : **Purple**Quantity per pot : **100****Norms**✓ EN 60998-1:2004 ;
EN60998-2-2:2004**Benefits**

- Test point for quick checking of the connection.

Compliance marks**GENERAL INFORMATION****Technical details**

Glow wire test: 960 °C < 5 s (NF EN 60 998-2-2).

Operating temperature: -30 °C to +105 °C.

For solid wires from 1 to 2.5 mm².

Material: polycarbonate colored body and polyamide 6.6 white door.

Voltage: 450 V.

Intensity: 24 A.

Instructions

1. Strip off 11 mm.

**ADDITIONAL INFORMATION**

Connection rail material: brass.

Contact tab material: stainless steel.



LOGISTIC INFORMATION

Packaging

**Bucket**

Height (cm) : 10

Length (cm) : 7,3

Depth (cm) : 7,3

Net weight (kg) : 0,092

Gross weight (kg) : 0,126



3 700882 193711

Outer package 1



x 10.00

Carton box

Height (cm) : 12,5

Length (cm) : 39

Depth (cm) : 16,5

Net weight (kg) : 0,92

Gross weight (kg) : 1,4



3 700882 198013

Outer package 2



x 40.00

Carton box

Height (cm) : 39

Length (cm) : 52

Depth (cm) : 17

Net weight (kg) : 3,68

Gross weight (kg) : 5,8



3 700882 198099

Outer package 3



x 1120.00

Pallet

Height (cm) : 120

Length (cm) : 80

Depth (cm) : 120

Net weight (kg) : 103,04

Gross weight (kg) : 185



3 700882 198174