

CHRISTA'L push wire connector 3 way orange (x 100)**Characteristics**Number of inputs : **3**Colour : **Orange**Quantity per pot : **100****Norms**✓ EN 60998-1:2004 ;
EN60998-2-2:2004**Benefits**

- Test point for quick checking of the connection.

Compliance marks**GENERAL INFORMATION****Technical details**

Glow wire test: 960 °C < 5 s (NF EN 60 998-2-2).

Operating temperature: -30 °C to +105 °C.

For solid wires from 1 to 2.5 mm².

Material: polycarbonate colored body and polyamide 6.6 white door.

Voltage: 450 V.

Intensity: 24 A.

Instructions

1. Strip off 11 mm.

**ADDITIONAL INFORMATION**

Connection rail material: brass.

Contact tab material: stainless steel.



LOGISTIC INFORMATION

 Packaging**Bucket**

Height (cm) : 10

Length (cm) : 7,3

Depth (cm) : 7,3

 Net weight (kg) : 0,128 Gross weight (kg) : 0,162

3 700882 193728

 Outer package 1

x 10.00

Carton box

Height (cm) : 12,5

Length (cm) : 39

Depth (cm) : 16,5

 Net weight (kg) : 1,28 Gross weight (kg) : 1,8

3 700882 198020

 Outer package 2

x 40.00

Carton box

Height (cm) : 39

Length (cm) : 52

Depth (cm) : 17

 Net weight (kg) : 5,12 Gross weight (kg) : 7,4

3 700882 198105

 Outer package 3

x 1120.00

Pallet

Height (cm) : 120

Length (cm) : 80

Depth (cm) : 120

 Net weight (kg) : 143,36 Gross weight (kg) : 230

3 700882 198181