

CHRISTA'L push wire connector 5 way blue (x 50)



Characteristics

Number of inputs : **5**
 Colour : **Blue**
 Quantity per pot : **50**

Norms

✓ EN 60998-1:2004 ;
 EN60998-2-2:2004

Benefits

- Test point for quick checking of the connection.

Compliance marks



GENERAL INFORMATION

Technical details

Glow wire test: 960 °C < 5 s (NF EN 60 998-2-2).
 Operating temperature: -30 °C to +105 °C.
 For solid wires from 1 to 2.5 mm².
 Material: polycarbonate colored body and polyamide 6.6 white door.
 Voltage: 450 V.
 Intensity: 24 A.

Instructions

1. Strip off 11 mm.

ADDITIONAL INFORMATION

Connection rail material: brass.
 Contact tab material: stainless steel.

LOGISTIC INFORMATION

Packaging



Bucket

Height (cm) : 10
 Length (cm) : 7,3
 Depth (cm) : 7,3
 Net weight (kg) : 0,102
 Gross weight (kg) : 0,136



3 700882 193742

Outer package 1



x 10.00

Carton box

Height (cm) : 12,5
 Length (cm) : 39
 Depth (cm) : 16,5
 Net weight (kg) : 1,02
 Gross weight (kg) : 1,5



3 700882 198044

Outer package 2



x 40.00

Carton box

Height (cm) : 39
 Length (cm) : 52
 Depth (cm) : 17
 Net weight (kg) : 4,08
 Gross weight (kg) : 6,2



3 700882 198129

Outer package 3



x 1120.00

Pallet

Height (cm) : 120
 Length (cm) : 80
 Depth (cm) : 120
 Net weight (kg) : 114,24
 Gross weight (kg) : 200



3 700882 198204