

CHRISTA'L push wire connector 8 way black (x 50)



Characteristics

Number of inputs : **8**
 Colour : **Black**
 Quantity per pot : **50**

Norms

✓ EN 60998-1:2004 ;
 EN60998-2-2:2004

Benefits

- Test point for quick checking of the connection.

Compliance marks



GENERAL INFORMATION

Technical details

Glow wire test: 960 °C < 5 s (NF EN 60 998-2-2).
 Operating temperature: -30 °C to +105 °C.
 For solid wires from 1 to 2.5 mm².
 Material: polycarbonate colored body and polyamide 6.6 white door.
 Voltage: 450 V.
 Intensity: 24 A.

Instructions

1. Strip off 11 mm.

ADDITIONAL INFORMATION

Connection rail material: brass.
 Contact tab material: stainless steel.



LOGISTIC INFORMATION

Packaging

**Bucket**

Height (cm) : 10

Length (cm) : 7,3

Depth (cm) : 7,3

Net weight (kg) : 0,194

Gross weight (kg) : 0,228



3 700882 193766

Outer package 1



x 10.00

Carton box

Height (cm) : 12,5

Length (cm) : 39

Depth (cm) : 16,5

Net weight (kg) : 1,94

Gross weight (kg) : 2,4



3 700882 198068

Outer package 2



x 40.00

Carton box

Height (cm) : 39

Length (cm) : 52

Depth (cm) : 17

Net weight (kg) : 7,76

Gross weight (kg) : 9,8



3 700882 198143

Outer package 3



x 1120.00

Pallet

Height (cm) : 120

Length (cm) : 80

Depth (cm) : 120

Net weight (kg) : 217,28

Gross weight (kg) : 305



3 700882 198228