

CHRISTA'L push wire connector Mixed 20 x 2 / 30 x 3 / 10 x 4 / 30 x 5 / 10 x 8 (x 100)



Characteristics

Number of inputs : -

Quantity per pot : **100 mixed terminals**

Norms

✓ EN 60998-1:2004 ;
EN60998-2-2:2004

Benefits

- Test point for quick checking of the connection.

Compliance marks



GENERAL INFORMATION

Technical details

Glow wire test: 960 °C < 5 s (NF EN 60 998-2-2).

Operating temperature: -30 °C to +105 °C.

For solid wires from 1 to 2.5 mm².

Material: polycarbonate colored body and polyamide 6.6 white door.

Voltage: 450 V.

Intensity: 24 A.

Instructions

1. Strip off 11 mm.



ADDITIONAL INFORMATION

Connection rail material: brass.
Contact tab material: stainless steel.



LOGISTIC INFORMATION

Packaging



Bucket

Height (cm) : 10

Length (cm) : 7,3

Depth (cm) : 7,3

Net weight (kg) : 0,162

Gross weight (kg) : 0,196



3 700882 194770

Outer package 1



x 10.00

Carton box

Height (cm) : 12,5

Length (cm) : 39

Depth (cm) : 16,5

Net weight (kg) : 1,62

Gross weight (kg) : 2,1



3 700882 198075

Outer package 2



x 40.00

Carton box

Height (cm) : 39

Length (cm) : 52

Depth (cm) : 17

Net weight (kg) : 6,48

Gross weight (kg) : 8,6



3 700882 198150

Outer package 3



x 1120.00

Pallet

Height (cm) : 120

Length (cm) : 80

Depth (cm) : 120

Net weight (kg) : 181,44

Gross weight (kg) : 265



3 700882 198235