

CHRISTA'L push wire connector 12 way green (x 25)



Characteristics

Number of inputs : **12**Colour : **Green**Quantity per pot : **25**

Norms

EN 60998-1:2004 ;
EN60998-2-2:2004

Benefits

- Test point for quick checking of the connection.

Compliance marks



GENERAL INFORMATION

■ Technical details

Glow wire test: 960 °C < 5 s (NF EN 60 998-2-2).

Operating temperature: -30 °C to +105 °C.

For solid wires from 1 to 2.5 mm².

Material: polycarbonate colored body and polyamide 6.6 white door.

Voltage: 450 V.

Intensity: 24 A.

■ Instructions

1. Strip off 11 mm.

i ADDITIONAL INFORMATION

Connection rail material: brass.

Contact tab material: stainless steel.

LOGISTIC INFORMATION

Packaging



Bucket

Height (cm) : 10
 Length (cm) : 7,3
 Depth (cm) : 7,3
 Net weight (kg) : 0,09
 Gross weight (kg) : 0,124



Outer package 1



Carton box

Height (cm) : 12,5
 Length (cm) : 39
 Depth (cm) : 16,5
 Net weight (kg) : 0,9
 Gross weight (kg) : 1,4



x 10.00

Outer package 2



Carton box

Height (cm) : 39
 Length (cm) : 52
 Depth (cm) : 17
 Net weight (kg) : 3,6
 Gross weight (kg) : 5,8



x 40.00

Outer package 3



Pallet

Height (cm) : 120
 Length (cm) : 80
 Depth (cm) : 120
 Net weight (kg) : 100,8
 Gross weight (kg) : 185



x 1120.00